



Project / Job Name:

Location:

Fixture Type:

Notes:

S15148 - 9.5 Watt A19 LED; 4000K CCT; 80 CRI;
Candelabra Base; Plastic; Dimmable; 120 Volt



GENERAL

Company	SATCO
EA Height	4.72
EA Width	2.36
EA Length	2.36
Lamp Filament	LED
Material	Plastic
Fixture Type	Miniature
Status	Active
Surge Protection	Built-in-surge protection - 0.5KV
CCT Selectable	No
Wattage Selectable	No
Finish Family	White
Amps	0.095A
Operating Position	Universal
Power Factor	>0.7
SDS Class	LED_Lamp
Shatter Proof Type	Polycarbonate
Indoor Outdoor	Indoor
Product Technology	LED
Incandescent Equivalent	60W

ELECTRICAL

CCT (Kelvin Temp)	4000K
Dimmable	Yes-Dimmable
Hours Rated	25000
Beam Angle (degree)	180
Color Temp	Cool White
CRI	80+
Dimming Type	Linear Dimming, Phase cut
Operating Frequency	50/60Hz
Operating Temp	-13F to +113F (-25C to +45C)
Lumens	800L
Volts	120v
Watts	9.5W

PHYSICAL

Lamp Base	Candelabra
Finish	Frost
ANSI Base	E12
Lamp Type	A19
MOD Lamps	2.36
MOL	4.72

ADDITIONAL INFO

Warranty	3-Years
Rated For Enclosed Fixture	Yes

PACKAGING

UPC	045923151484
Case Cube	0.5179
Case Height	10.24
Case Length	10.83
Case Quantity	24
Case UPC	10045923151481
Case Weight	4.38
Case Width	8.07
EA Cube	0.0152
EA Height	4.72
EA Length	2.36
EA Quantity	1
EA Weight	0.13
EA Width	2.36
Inner Cube	0.1046
Inner Height	4.72
Inner Length	7.48
Inner Quantity	6
Inner UPC	20045923151488
Inner Weight	0.94
Inner Width	5.12
Pack Type	Color Box
Web Length	4.72
Web Width	2.36

COMPLIANCE

CA Prop 65	Lead
Dark Sky Rated	No
FCC Compliant	Yes
Location Rating	Damp
NSF Approved	No
ROHS Compliant	Yes
Safety Listing	cULus - Certified, cULus - Listed
California Ban	Non-Compliant
Title 20	No
T24/JA8 Compliant	No
US State Ban	CA