



Project / Job Name:

Location:

Fixture Type:

Notes:

**S15200** - 5.5 Watt A15 LED; 2700K CCT; 80 CRI; Candelabra Base; Plastic; Dimmable; 120 Volt



#### GENERAL

|                         |                                   |
|-------------------------|-----------------------------------|
| Company                 | SATCO                             |
| EA Height               | 3.35                              |
| EA Width                | 1.77                              |
| EA Length               | 1.77                              |
| Lamp Filament           | LED                               |
| Material                | Plastic                           |
| Fixture Type            | Miniature                         |
| Status                  | Active                            |
| Surge Protection        | Built-in-surge protection - 0.5KV |
| CCT Selectable          | No                                |
| Wattage Selectable      | No                                |
| Finish Family           | White                             |
| Amps                    | 0.060A                            |
| Operating Position      | Universal                         |
| Power Factor            | >0.7                              |
| SDS Class               | LED_Lamp                          |
| Shatter Proof Type      | Polycarbonate                     |
| Indoor Outdoor          | Indoor                            |
| Product Technology      | LED                               |
| Incandescent Equivalent | 40W                               |

#### ELECTRICAL

|                     |                              |
|---------------------|------------------------------|
| CCT (Kelvin Temp)   | 2700K                        |
| Dimmable            | Yes-Dimmable                 |
| Hours Rated         | 25000                        |
| Beam Angle (degree) | 180                          |
| Color Temp          | Warm White                   |
| CRI                 | 80+                          |
| Dimming Type        | Linear Dimming, Phase cut    |
| Operating Frequency | 50/60Hz                      |
| Operating Temp      | -13F to +113F (-25C to +45C) |
| Lumens              | 450L                         |
| Volts               | 120v                         |
| Watts               | 5.5W                         |

#### PHYSICAL

|           |            |
|-----------|------------|
| Lamp Base | Candelabra |
| Finish    | Frost      |
| ANSI Base | E12        |
| Lamp Type | A15        |
| MOD Lamps | 1.77       |
| MOL       | 3.07       |

#### ADDITIONAL INFO

|                            |         |
|----------------------------|---------|
| Warranty                   | 3-Years |
| Rated For Enclosed Fixture | Yes     |

#### PACKAGING

|                |                |
|----------------|----------------|
| UPC            | 045923152009   |
| Case Cube      | 0.2485         |
| Case Height    | 7.87           |
| Case Length    | 8.66           |
| Case Quantity  | 24             |
| Case UPC       | 10045923152006 |
| Case Weight    | 2.34           |
| Case Width     | 6.3            |
| EA Cube        | 0.0061         |
| EA Height      | 3.35           |
| EA Length      | 1.77           |
| EA Quantity    | 1              |
| EA Weight      | 0.07           |
| EA Width       | 1.77           |
| Inner Cube     | 0.0461         |
| Inner Height   | 3.54           |
| Inner Length   | 5.71           |
| Inner Quantity | 6              |
| Inner UPC      | 20045923152003 |
| Inner Weight   | 0.49           |
| Inner Width    | 3.94           |
| Pack Type      | Color Box      |
| Web Length     | 3.07           |
| Web Width      | 1.77           |

#### COMPLIANCE

|                   |                                   |
|-------------------|-----------------------------------|
| CA Prop 65        | Lead                              |
| Dark Sky Rated    | No                                |
| FCC Compliant     | Yes                               |
| Location Rating   | Damp                              |
| NSF Approved      | No                                |
| ROHS Compliant    | Yes                               |
| Safety Listing    | cULus - Certified, cULus - Listed |
| California Ban    | Non-Compliant                     |
| Title 20          | No                                |
| T24/JA8 Compliant | No                                |
| US State Ban      | CA                                |