



Project / Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**S16510** - LED Circline; 11 Watt; T9; 3000K/4000K/6500K  
CCT Selectable; G10q Base; 120-277 Volt



**GENERAL**

Company	SATCO
EA Height	8.46
EA Width	1.38
EA Length	8.46
Lamp Ballast Type AB	Type A/B
Ballasting Requirements	Ballast required (Type A, Electronic only) or Ballast Bypass (Type B)
Lamp Filament	LED
Material	Polycarbonate (PC)
Fixture Type	Circline
Product Notes	Only compatible with Electronic ballasts when installed in Type A mode. See ballast compatibility list for details. Not for use on magnetic ballasts.; Inner Diameter: 5.71 in.
Status	Active
Style	Utility
Surge Protection	Built-in surge protection - 2.5KV
Total Harmonic Distortion	25%
CCT Selectable	Yes
Wattage Selectable	No
Finish Family	White
Amps	0.092-0.040A
Has Camera	No
IOT Enabled	No
Lens Finish	Frost
Minimum Compartment Size	Length 11.4 in. Width 11.4 in. Height: 3.5 in.
SDS Class	LED_Lamp
Indoor Outdoor	Indoor
Product Technology	LED
Fluor Equiv	22W
Incandescent Equivalent	50W

**PACKAGING**

UPC	045923165108
Case Cube	0.7868
Case Height	8.86
Case Length	17.32
Case Quantity	12
Case UPC	10045923165105
Case Weight	7.34
Case Width	8.86
EA Cube	0.0572
EA Height	8.46
EA Length	8.46
EA Quantity	1
EA Weight	0.6
EA Width	1.38
Pack Type	Box
Web Length	8.08
Web Width	1.2

**COMPLIANCE**

FCC Compliant	Yes
Location Rating	Damp
ROHS Compliant	Yes
Safety Listing	cETLus - Classified
California Ban	Lawful for sale
DLC Approved	No
Title 20	Exempt
T24 Compliant	No

**ELECTRICAL**

CCT (Kelvin Temp)	3000K/4000K/6500K
Dimmable	Non-Dimmable
Hours Rated	50000
Beam Angle (degree)	180
Color Temp	Soft White to Daylight
CRI	80+
Operating Frequency	50/60Hz
Operating Temp	-20C (-4F) to +45C (+113F)
Lumens	1300L/1400L/1350L
Volts	120V-277V
Watts	11W

**PHYSICAL**

Lamp Base	G10q (4-Pin)
Finish	Frost
Housing Color	Frost
ANSI Base	G10q
Lamp Type	T9
MOD Lamps	1.2
MOL	8.08

**ADDITIONAL INFO**

Warranty	5-Years
Installation Notes	Not for use in vapor tight fixtures.
Rated For Enclosed Fixture	Yes