



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S18414 - 11.5/13/15 Wattage Selectable T8 U-Bend LED; 30K/35K/40K/50K/65K CCT Selectable; 1-Inch; Frost Finish; 120-277 Range Voltage



GENERAL

Company	SATCO
EA Height	2.83
EA Width	1.22
EA Length	23.03
Lamp Ballast Type AB	Type A/B
Ballasting Requirements	Ballast required (Type A) or Ballast Bypass (Type B)
Lamp Filament	LED
Material	Glass
Fixture Type	U-Bend
Status	Active
Style	Utility
Total Harmonic Distortion	<20%
CCT Selectable	Yes
Wattage Selectable	Yes
Finish Family	White
Amps	0.192A
Has Camera	No
IOT Enabled	No
Leg Spacing	1.63
Lens Finish	Frost
Lens Material	Glass
Power Factor	>0.9
SDS Class	LED_Lamp
Indoor Outdoor	Indoor
Product Technology	LED
Fluor Equiv	32W
Incandescent Equivalent	50W

ELECTRICAL

CCT (Kelvin Temp)	3000K/3500K/4000K/5000K/6500K
Dimmable	Yes-Dimmable
Hours Rated	50000
Beam Angle (degree)	210
Color Temp	Soft White to Daylight
CRI	80+
Dimming Type	Check Ballast MFG for Dimmer Compatibility, Only in Type A mode
Operating Frequency	50/60Hz
Operating Temp	-4F to +113F (-20C to +45C)
Lumens	1800L/2000L/2200L
Volts	120V-277V
Watts	11.5W/13W/15W

PHYSICAL

Lamp Base	Medium Bi Pin
Finish	Frost
Housing Color	White
ANSI Base	G13
Lamp Type	T8
MOD Lamps	0.96
MOL	22.43

ADDITIONAL INFO

Warranty	5-Years
Installation Notes	Not for use in vapor tight fixtures.
Rated For Enclosed Fixture	No

PACKAGING

UPC	045923184147
Case Cube	0.6587
Case Height	9.06
Case Length	23.66
Case Quantity	12
Case UPC	10045923184144
Case Weight	8.53
Case Width	5.31
EA Cube	0.046
EA Height	2.83
EA Length	23.03
EA Quantity	1
EA Weight	0.64
EA Width	1.22
Pack Type	Box
Web Length	22.43
Web Width	0.96

COMPLIANCE

DLC ID	S-H5FJF9
FCC Compliant	Yes
Location Rating	Damp
NSF Approved	Yes
ROHS Compliant	Yes
Safety Listing	cULus - Certified, cULus - Classified, cULus - Listed
California Ban	Lawful for sale
DLC Approved	Yes
Title 20	Exempt
T24 Compliant	No