



Project / Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**S18417** - 10 Watt PLL LED; 2G11 Base;  
30K/35K/40K/50K/65K CCT Selectable; Type A/B; 120-277 Volt



### GENERAL

Company	SATCO
EA Height	0.98
EA Width	1.77
EA Length	12.99
Lamp Ballast Type AB	Type A/B
Dimmable Text	Reverse Phase; 120V only
Lamp Filament	LED
Material	Glass / Plastic
Fixture Type	Miniature
Status	Active
Surge Protection	Built-in-surge protection - 0.5KV
Total Harmonic Distortion	<20%
CCT Selectable	Yes
Wattage Selectable	No
Finish Family	White
Amps	0.085A
IOT Enabled	No
Nominal Length	13.0
Operating Position	Universal
Power Factor	>0.9
SDS Class	LED_Lamp
Shatter Proof Type	PET Coated
Product Technology	LED
Fluor Equiv	24W

### ELECTRICAL

CCT (Kelvin Temp)	3000K/3500K/4000K/5000K/6500K
Dimmable	Yes-Dimmable
Hours Rated	50000
Beam Angle (degree)	160
Color Temp	Soft White to Daylight
CRI	80+
Dimming Type	120V only, Phase cut
Operating Frequency	50/60Hz
Operating Temp	-20C (-4F) to +45C (+113F)
Lumens	1250L
Volts	120V-277V
Watts	10W

### PHYSICAL

Lamp Base	4-Pin
Finish	Frost
Housing Color	White
ANSI Base	2G11
Lamp Type	T5
MOD Lamps	1.72
MOL	12.9

### ADDITIONAL INFO

Warranty	5-Years
Rated For Enclosed Fixture	Yes

### PACKAGING

UPC	045923184178
Case Cube	0.4394
Case Height	5.71
Case Length	13.78
Case Quantity	25
Case UPC	10045923184175
Case Weight	12.32
Case Width	9.65
EA Cube	0.013
EA Height	0.98
EA Length	12.99
EA Quantity	1
EA Weight	0.46
EA Width	1.77
Pack Type	Color Box
Web Length	12.9
Web Width	1.72

### COMPLIANCE

ADA Compliant	No
FCC Compliant	Yes
IP Rating	IP20
Location Rating	Damp
NSF Approved	Yes
ROHS Compliant	Yes
Safety Listing	cULus - Certified, cULus - Classified
California Ban	Lawful for sale
Title 20	Exempt
T24 Compliant	No