



Project / Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**S1912** - 75 Watt; Halogen; T4; Frosted; 2000 Average rated hours; 1290 Lumens; Bi Pin GY6.35 base; 12 Volt



**GENERAL**

|                    |  |
|--------------------|--|
| Company            | SATCO                                  |
| EA Height          | 0.87                                   |
| EA Width           | 0.87                                   |
| EA Length          | 2.68                                   |
| Lamp Filament      | C-6                                    |
| Fixture Type       | Bi-Pin                                 |
| Status             | Discontinued                           |
| CCT Selectable     | No                                     |
| Wattage Selectable | No                                     |
| Finish Family      | White                                  |
| Amps               | 6.250A                                 |
| Has Camera         | No                                     |
| IOT Enabled        | No                                     |
| Lens Finish        | Frost                                  |
| Lensed             | Yes                                    |
| Operating Position | Universal                              |
| SDS Class          | Halogen_Double_Ended_or_Pin_Based_Lamp |
| Product Technology | Halogen                                |

**ELECTRICAL**

|                     |                        |
|---------------------|------------------------|
| CCT (Kelvin Temp)   | 2900K                  |
| Dimmable            | Yes-Dimmable           |
| Hours Rated         | 2000                   |
| Beam Angle (degree) | 360                    |
| Color Temp          | Warm White             |
| CRI                 | 100                    |
| Dimming Type        | Low Voltage, Phase cut |
| Lumens              | 1290L                  |
| Volts               | 12V                    |
| Watts               | 75W                    |

**PHYSICAL**

|           |               |
|-----------|---------------|
| Lamp Base | Bi Pin GY6.35 |
| Finish    | Frost         |
| ANSI Base | GY6.35        |
| Lamp Type | T4            |
| MOD Lamps | 0.5           |
| MOL       | 1.56          |

**PACKAGING**

|                |                |
|----------------|----------------|
| UPC            | 045923019128   |
| Case Cube      | 1.7598         |
| Case Height    | 12.61          |
| Case Length    | 29.16          |
| Case Quantity  | 960            |
| Case UPC       | 10045923019125 |
| Case Weight    | 11.03          |
| Case Width     | 8.27           |
| EA Cube        | 0.0012         |
| EA Height      | 0.87           |
| EA Length      | 2.68           |
| EA Quantity    | 1              |
| EA Weight      | 0.01           |
| EA Width       | 0.87           |
| Inner Cube     | 0.0723         |
| Inner Height   | 5.79           |
| Inner Length   | 5.59           |
| Inner Quantity | 48             |
| Inner UPC      | 20045923019122 |
| Inner Weight   | 0.53           |
| Inner Width    | 3.86           |
| Pack Type      | Box            |
| Web Length     | 1.56           |
| Web Width      | 0.5            |

**COMPLIANCE**

|                   |                 |
|-------------------|-----------------|
| CA Prop 65        | Lead            |
| Location Rating   | Damp            |
| ROHS Compliant    | Yes             |
| Safety Listing    | Not Applicable  |
| California Ban    | Lawful for sale |
| DLC Approved      | No              |
| Title 20          | Exempt          |
| T24/JA8 Compliant | No              |