



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S1957 - 20 Watt; Halogen; MR16; ESX; 2000 Average rated hours; Miniature 2 Pin Round base; 12 Volt



GENERAL

Company	SATCO
EA Height	4.38
EA Width	2.38
EA Length	1.38
Candle Power	2200.0
Center Beam Candle Power	2200
Dimmable Text	Check the transformer/driver MFG for dimmer compatibility
Lamp Filament	C-8
Fixture Type	MR
Spot Type	NSP - Narrow Spot
Status	Active
CCT Selectable	No
Wattage Selectable	No
Finish Family	No Finish
Additional Info	UV Block
Amps	1.667A
Has Camera	No
IOT Enabled	No
Lens Finish	Clear
Lensed	No
Operating Position	Universal
SDS Class	Halogen_Double_Ended_or_Pin_Based_Lamp
Product Technology	Halogen

ELECTRICAL

CCT (Kelvin Temp)	2900K
Dimmable	Yes-Dimmable
Hours Rated	2000
Beam Angle (degree)	9
Color Temp	Warm White
CRI	100
Dimming Type	Check the transformer/driver MFG for dimmer compatibility
Lumens	180L
Volts	12V
Watts	20W

PHYSICAL

Lamp Base	Miniature 2 Pin Round
Finish	Clear
Housing Color	Clear
ANSI Base	GU5.3/GX5.3
Lamp Type	MR16
MOD Lamps	2.0
MOL	1.88

PACKAGING

UPC	045923019579
Case Cube	1.6294
Case Height	12.0
Case Length	17.38
Case Quantity	240
Case UPC	10045923019576
Case Weight	19.75
Case Width	13.5
EA Cube	0.0083
EA Height	4.38
EA Length	1.38
EA Quantity	1
EA Weight	0.08
EA Width	2.38
Inner Cube	0.0719
Inner Height	2.25
Inner Length	8.5
Inner Quantity	12
Inner UPC	20045923019573
Inner Weight	1.34
Inner Width	6.5
Pack Type	Box
Web Length	1.88
Web Width	2.0

COMPLIANCE

CA T20 Compliant Substitute	S9491
CA Prop 65	Lead
Location Rating	Damp
MA Alt Sub	S9552
NV Alt Sub	S9552
ROHS Compliant	Yes
Safety Listing	Not Applicable
California Ban	Non-Compliant
DLC Approved	No
Title 20	No
T24 Compliant	No
US State Ban	CA, MA, NV