



Project / Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**S1991** - 35 Watt; Halogen; MR11; FTE/C/24; 2000 Average rated hours; Sub Miniature 2 Pin base; 24 Volt



**GENERAL**

|                          |   |
|--------------------------|---|
| Company                  | SATCO   |
| EA Height                | 1.57  |
| EA Width                 | 1.57  |
| EA Length                | 1.77  |
| Center Beam Candle Power | 4500  |
| Dimmable Text            | Check the transformer/driver MFG for dimmer compatibility |
| Lamp Filament            | C-6   |
| Fixture Type             | MR  |
| Spot Type                | NSP - Narrow Spot   |
| Status                   | Discontinued  |
| CCT Selectable           | No  |
| Wattage Selectable       | No  |
| Finish Family            | No Finish   |
| Additional Info          | UV Block  |
| Amps                     | 1.458A  |
| Has Camera               | No  |
| IOT Enabled              | No  |
| Lens Finish              | Clear   |
| Lensed                   | Yes   |
| Operating Position       | Universal   |
| SDS Class                | Halogen_Double_Ended_or_Pin_Based_Lamp                    |
| Product Technology       | Halogen   |

**ELECTRICAL**

|                     |   |
|---------------------|---|
| CCT (Kelvin Temp)   | 2900K   |
| Dimmable            | Yes-Dimmable  |
| Hours Rated         | 2000  |
| Beam Angle (degree) | 9   |
| Color Temp          | Warm White  |
| CRI                 | 100   |
| Dimming Type        | Check the transformer/driver MFG for dimmer compatibility |
| Lumens              | 285L  |
| Volts               | 24V   |
| Watts               | 35W   |

**PHYSICAL**

|               |            |
|---------------|------------|
| Lamp Base     | Bi Pin G24 |
| Finish        | Clear      |
| Housing Color | Clear      |
| ANSI Base     | G24        |
| Lamp Type     | MR11       |
| MOD Lamps     | 1.38       |
| MOL           | 1.25       |

**PACKAGING**

|                |                |
|----------------|----------------|
| UPC            | 045923019913   |
| Case Cube      | 0.9643         |
| Case Height    | 10.84          |
| Case Length    | 14.18          |
| Case Quantity  | 240            |
| Case UPC       | 10045923019910 |
| Case Weight    | 11.58          |
| Case Width     | 10.84          |
| EA Cube        | 0.0025         |
| EA Height      | 1.57           |
| EA Length      | 1.77           |
| EA Quantity    | 1              |
| EA Weight      | 0.04           |
| EA Width       | 1.57           |
| Inner Cube     | 0.0396         |
| Inner Height   | 1.97           |
| Inner Length   | 6.78           |
| Inner Quantity | 12             |
| Inner UPC      | 20045923019917 |
| Inner Weight   | 0.55           |
| Inner Width    | 5.12           |
| Pack Type      | Box            |
| Web Length     | 1.25           |
| Web Width      | 1.38           |

**COMPLIANCE**

|                 |                |
|-----------------|----------------|
| CA Prop 65      | Lead           |
| Location Rating | Damp           |
| ROHS Compliant  | Yes            |
| Safety Listing  | Not Applicable |
| California Ban  | Non-Compliant  |
| DLC Approved    | No             |
| Title 20        | No             |
| T24 Compliant   | No             |
| US State Ban    | CA             |