

S19946 - 11 Watt; 2 Foot; T5 LED; Miniature Bi Pin Base; 3500K; Type A; 1350 Lumens


GENERAL

Company	SATCO
EA Height	0.65
EA Width	0.65
EA Length	22.17
Lamp Ballast Type AB	Type A
Ballasting Requirements	Ballast required, check compatibility
Lamp Filament	LED
Material	Aluminum / Glass
Fixture Type	Type A
Status	Active
Style	Utility
Total Harmonic Distortion	20%
CCT Selectable	No
Wattage Selectable	No
Finish Family	White
Additional Info	Light Emitting Area of 325 degrees; System Wattage (Type A) - 14W
Amps	0.092-0.040A
Has Camera	No
IOT Enabled	No
Lens Material	Glass
Nominal Length	24.0
Operating Position	Universal
Power Factor	0.9
SDS Class	LED_Lamp
Indoor Outdoor	Indoor
Product Technology	LED
Fluor Equiv	24W
Incandescent Equivalent	50W

PACKAGING

UPC	045923199462
Case Cube	0.2209
Case Height	3.94
Case Length	23.86
Case Quantity	25
Case UPC	10045923199469
Case Weight	3.93
Case Width	4.06
EA Cube	0.0054
EA Height	0.65
EA Length	22.17
EA Quantity	1
EA Weight	0.14
EA Width	0.65
Pack Type	Sleeve
Web Length	22.5
Web Width	0.63

COMPLIANCE

FCC Compliant	Yes
Location Rating	Damp
NSF Approved	Yes
ROHS Compliant	Yes
Safety Listing	cULus - Certified, cULus - Listed
California Ban	Lawful for sale
DLC Approved	No
Title 20	Exempt
T24/JA8 Compliant	No

ELECTRICAL

CCT (Kelvin Temp)	3500K
Dimmable	Yes-Dimmable
Hours Rated	50000
Beam Angle (degree)	185
Color Temp	Neutral White
CRI	80+
Dimming Type	Check Ballast MFG for Dimmer Compatibility, Only in Type A mode
Operating Frequency	50/60Hz
Operating Temp	-4F to +113F (-20C to +45C)
Lumens	1350L
Volts	Ballast Dependent
Watts	11W

PHYSICAL

Lamp Base	Miniature Bi Pin
Finish	WHITE
Housing Color	None
ANSI Base	G5
Lamp Type	T5
MOD Lamps	0.63
MOL	22.5

ADDITIONAL INFO

Warranty	5-Years
Installation Notes	Not for use in vapor tight fixtures.
Rated For Enclosed Fixture	Yes