



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S19956 - 12 Watt T5 LED; 36 Inch; 4000K CCT; Omni Type A+B; PET Coated; Line Voltage Dimmable; 120-277 Volt



GENERAL

Company	SATCO
EA Height	0.75
EA Width	0.75
EA Length	33.86
Lamp Ballast Type AB	Type A/B
Lamp Filament	LED
Material	Plastic
Fixture Type	Miniature
Status	Active
Surge Protection	Built-in-surge protection - 0.5KV
Total Harmonic Distortion	<20%
CCT Selectable	No
Wattage Selectable	No
Finish Family	White
Amps	0.110-0.050A
IOT Enabled	No
Lens Finish	Frost
Lens Material	Glass
Nominal Length	36.0
Operating Position	Universal
Power Factor	>0.9
SDS Class	LED_Lamps
Shatter Proof Type	PET Coated
Indoor Outdoor	Indoor
Product Technology	LED
Fluor Equiv	21W

ELECTRICAL

CCT (Kelvin Temp)	4000K
Dimmable	Yes-Dimmable
Hours Rated	50000
Beam Angle (degree)	180
Color Temp	Cool White
CRI	80+
Dimming Type	120V only, Phase cut
Operating Frequency	50/60Hz
Operating Temp	-4F to +113F (-20C to +45C)
Lumens	1620L
Volts	120V-277V
Watts	12W

PHYSICAL

Lamp Base	Miniature Bi Pin
Finish	Frost
ANSI Base	G5
Lamp Type	T5
MOD Lamps	0.62
MOL	33.94

ADDITIONAL INFO

Warranty	5-Years
Rated For Enclosed Fixture	Yes

PACKAGING

UPC	045923199561
Case Cube	0.4308
Case Height	4.72
Case Length	36.42
Case Quantity	25
Case UPC	10045923199568
Case Weight	6.5
Case Width	4.33
EA Cube	0.011
EA Height	0.75
EA Length	33.86
EA Quantity	1
EA Weight	0.26
EA Width	0.75
Pack Type	Sleeve
Web Length	33.94
Web Width	0.62

COMPLIANCE

Dark Sky Rated	No
FCC Compliant	Yes
IP Rating	IP20
Location Rating	Damp
NSF Approved	Yes
ROHS Compliant	Yes
Safety Listing	cRUus - Recognized Component, cULus - Certified, cULus - Classified
California Ban	Lawful for sale
Title 20	Exempt
T24 Compliant	No