

S19962 - 15 Watt T5 LED; 48 Inch; 4000K CCT; Omni Type A+B; PET Coated; Line Voltage Dimmable; 120-347 Volt


GENERAL

Company	SATCO
EA Height	0.75
EA Width	0.75
EA Length	45.67
Lamp Ballast Type AB	Type A/B
Dimmable Text	Reverse Phase; 120V only
Lamp Filament	LED
Material	Plastic
Fixture Type	Miniature
Status	Active
Surge Protection	Built-in-surge protection - 0.5KV
Total Harmonic Distortion	<20%
CCT Selectable	No
Wattage Selectable	No
Finish Family	White
Amps	0.130-0.040A
IOT Enabled	No
Lens Finish	Frost
Lens Material	Glass
Nominal Length	48.0
Operating Position	Universal
Power Factor	>0.9
SDS Class	LED_Lamps
Shatter Proof Type	PET Coated
Indoor Outdoor	Indoor
Product Technology	LED
Fluor Equiv	28W

ELECTRICAL

CCT (Kelvin Temp)	4000K
Dimmable	Yes-Dimmable
Hours Rated	50000
Beam Angle (degree)	180
Color Temp	Cool White
CRI	80+
Dimming Type	120V only, Phase cut
Operating Frequency	50/60Hz
Operating Temp	-20C (-4F) to +45C (+113F)
Lumens	1900L
Volts	120V-347V
Watts	15W

PHYSICAL

Lamp Base	Miniature Bi Pin
Finish	Frost
ANSI Base	G5
Lamp Type	T5
MOD Lamps	0.62
MOL	45.75

ADDITIONAL INFO

Warranty	5-Years
Rated For Enclosed Fixture	Yes

PACKAGING

UPC	045923199622
Case Cube	0.5704
Case Height	4.72
Case Length	48.23
Case Quantity	25
Case UPC	10045923199629
Case Weight	9.2
Case Width	4.33
EA Cube	0.0149
EA Height	0.75
EA Length	45.67
EA Quantity	1
EA Weight	0.34
EA Width	0.75
Inner Cube	0.0
Pack Type	Sleeve
Web Length	45.75
Web Width	0.62

COMPLIANCE

Dark Sky Rated	No
FCC Compliant	Yes
IP Rating	IP20
Location Rating	Damp
NSF Approved	Yes
ROHS Compliant	Yes
Safety Listing	cRUus - Recognized Component, cULus - Certified, cULus - Classified
California Ban	Lawful for sale
Title 20	Exempt
T24 Compliant	No