



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S21210 - 5.5 Watt G16.5 LED Filament; Clear; Candelabra base; 90 CRI; 3000K; 120 Volt



GENERAL

Company	SATCO
EA Height	3.62
EA Width	2.17
EA Length	2.17
Lamp Filament	LED Filament
Material	Glass / Nickel Plated Aluminum
Fixture Type	Globe
Status	Active
Style	Transitional
CCT Selectable	No
Wattage Selectable	No
Finish Family	Clear
Amps	0.062A
Has Camera	No
IOT Enabled	No
Operating Position	Universal
Power Factor	0.75
SDS Class	LED_Lamp
Indoor Outdoor	Indoor, Outdoor
Product Technology	LED
Incandescent Equivalent	60W

ELECTRICAL

CCT (Kelvin Temp)	3000K
Dimmable	Yes-Dimmable
Hours Rated	15000
Beam Angle (degree)	300
Color Temp	Soft White
CRI	90+
Dimming Type	120V only, Phase cut
Operating Frequency	60Hz
Operating Temp	-4F to +113F (-20C to +45C)
Lumens	500L
Volts	120v
Watts	5.5W

PHYSICAL

Lamp Base	Candelabra
Finish	Clear
Housing Color	None
ANSI Base	E12
Lamp Type	G16.5
MOD Lamps	1.97
MOL	3.11

ADDITIONAL INFO

Warranty	2-Years
Rated For Enclosed Fixture	Yes

PACKAGING

UPC	045923205255
Case Cube	0.3776
Case Height	4.45
Case Length	14.72
Case Quantity	24
Case UPC	10045923205252
Case Weight	2.78
Case Width	9.96
EA Cube	0.0099
EA Height	3.62
EA Length	2.17
EA Quantity	1
EA Weight	0.07
EA Width	2.17
Inner Cube	0.0752
Inner Height	4.02
Inner Length	6.89
Inner Quantity	6
Inner UPC	20045923205259
Inner Weight	0.54
Inner Width	4.69
Pack Type	Box
Web Length	3.11
Web Width	1.97

COMPLIANCE

FCC Compliant	Yes
Location Rating	Wet
NSF Approved	No
ROHS Compliant	Yes
Safety Listing	cULus - Certified, cULus - Listed
California Ban	Lawful for sale
UL Application	Filament LED Lamp
DLC Approved	No
Title 20	Yes
T24/JA8 Compliant	No