



Project / Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**S21372** - 4 Watt T6.5 LED Filament; Frosted; Intermediate Base; 3000K; 360 Lumens; 120 Volt



**GENERAL**

|                         |                 |
|-------------------------|-----------------|
| Company                 | SATCO           |
| EA Height               | 5.43            |
| EA Width                | 1.18            |
| EA Length               | 1.18            |
| Lamp Filament           | LED Filament    |
| Material                | Glass           |
| Fixture Type            | Tubular         |
| Status                  | Active          |
| Style                   | Transitional    |
| CCT Selectable          | No              |
| Wattage Selectable      | No              |
| Finish Family           | White           |
| Amps                    | 0.043A          |
| Has Camera              | No              |
| IOT Enabled             | No              |
| Operating Position      | Universal       |
| Power Factor            | >0.7            |
| SDS Class               | LED_Lamp        |
| Indoor Outdoor          | Indoor, Outdoor |
| Product Technology      | LED             |
| Incandescent Equivalent | 40W             |

**ELECTRICAL**

|                     |                             |
|---------------------|-----------------------------|
| CCT (Kelvin Temp)   | 3000K                       |
| Dimmable            | Yes-Dimmable                |
| Hours Rated         | 15000                       |
| Beam Angle (degree) | 300                         |
| Color Temp          | Soft White                  |
| CRI                 | 90+                         |
| Operating Frequency | 60Hz                        |
| Operating Temp      | -4F to +113F (-20C to +45C) |
| Lumens              | 360L                        |
| Volts               | 120v                        |
| Watts               | 4W                          |

**PHYSICAL**

|               |              |
|---------------|--------------|
| Lamp Base     | Intermediate |
| Finish        | Frost        |
| Housing Color | Frost        |
| ANSI Base     | E17          |
| Lamp Type     | T6.5         |
| MOD Lamps     | 0.79         |
| MOL           | 5.12         |

**ADDITIONAL INFO**

|                            |                                      |
|----------------------------|--------------------------------------|
| Warranty                   | 2-Years                              |
| Installation Notes         | Not for use in vapor tight fixtures. |
| Rated For Enclosed Fixture | Yes                                  |

**PACKAGING**

|                |                |
|----------------|----------------|
| UPC            | 045923231728   |
| Case Cube      | 0.1707         |
| Case Height    | 4.17           |
| Case Length    | 12.05          |
| Case Quantity  | 24             |
| Case UPC       | 10045923231725 |
| Case Weight    | 1.962          |
| Case Width     | 5.87           |
| EA Cube        | 0.0044         |
| EA Height      | 5.43           |
| EA Length      | 1.18           |
| EA Quantity    | 1              |
| EA Weight      | 0.07           |
| EA Width       | 1.18           |
| Inner Cube     | 0.065          |
| Inner Height   | 3.9            |
| Inner Length   | 5.67           |
| Inner Quantity | 12             |
| Inner UPC      | 20045923231722 |
| Inner Weight   | 0.96           |
| Inner Width    | 5.08           |
| Pack Type      | Box            |
| Web Length     | 5.12           |
| Web Width      | 0.79           |

**COMPLIANCE**

|                 |                   |
|-----------------|-------------------|
| FCC Compliant   | Yes               |
| Location Rating | Wet               |
| ROHS Compliant  | Yes               |
| Safety Listing  | cULus - Listed    |
| California Ban  | Lawful for sale   |
| UL Application  | Filament LED Lamp |
| DLC Approved    | No                |
| Title 20        | Yes               |
| T24 Compliant   | No                |