



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S21405 - 16 Watt LED PL 4-Pin; 3500K; 1750 Lumens; G24q base; 50000 Average rated hours; Vertical; Type A; Ballast dependent



GENERAL

Company	SATCO
EA Height	6.3
EA Width	3.86
EA Length	3.86
Lamp Ballast Type AB	Type A
Ballasting Requirements	Ballast required, check compatibility
Lamp Filament	LED
Fixture Type	PL
Status	Discontinued
Style	Transitional
Total Harmonic Distortion	20%
CCT Selectable	No
Wattage Selectable	No
Finish Family	White
Amps	0.133-0.058A
Has Camera	No
IOT Enabled	No
Lens Finish	Frost
Lensed	Yes
Operating Position	Base Up or Down
Power Factor	0.9
SDS Class	LED_Lamp
Product Technology	LED
Fluor Equiv	42W
Incandescent Equivalent	100W

ELECTRICAL

CCT (Kelvin Temp)	3500K
Hours Rated	50000
Beam Angle (degree)	110
Color Temp	Neutral White
CRI	80+
Operating Temp	-4F to +113F (-20C to +45C)
Lumens	1750L
Volts	Ballast Dependent
Watts	16W

PHYSICAL

Lamp Base	G24q (4-Pin)
Finish	Frost
ANSI Base	G24q
Lamp Type	PL
MOD Lamps	3.75
MOL	5.19

ADDITIONAL INFO

Warranty	5-Years
Rated For Enclosed Fixture	Yes

PACKAGING

UPC	045923224058
Case Cube	1.5156
Case Height	14.17
Case Length	20.86
Case Quantity	20
Case UPC	10045923224055
Case Weight	11.68
Case Width	8.86
EA Cube	0.0543
EA Height	6.3
EA Length	3.86
EA Quantity	1
EA Weight	0.33
EA Width	3.86
Inner Cube	0.6439
Inner Height	6.7
Inner Length	20.08
Inner Quantity	10
Inner UPC	20045923224052
Inner Weight	5.5
Inner Width	8.27
Pack Type	Box
Web Length	5.19
Web Width	3.75

COMPLIANCE

DLC ID	PLS86H65T77J
FCC Compliant	Yes
Location Rating	Damp
NSF Approved	Yes
ROHS Compliant	Yes
Safety Listing	cULus
California Ban	Lawful for sale
DLC Approved	Yes
Title 20	Exempt