



Project / Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**S21407** - 16 Watt LED PL 4-Pin; 5000K; 1850 Lumens; G24q base; 50000 Average rated hours; Vertical; Type A; Ballast dependent



### GENERAL

Company	SATCO
EA Height	6.3
EA Width	3.86
EA Length	3.86
Lamp Ballast Type AB	Type A
Ballasting Requirements	Ballast required, check compatibility
Lamp Filament	LED
Fixture Type	PL
Status	Discontinued
Style	Transitional
Total Harmonic Distortion	20%
CCT Selectable	No
Wattage Selectable	No
Finish Family	White
Amps	0.133-0.058A
Has Camera	No
IOT Enabled	No
Lens Finish	Frost
Lensed	Yes
Operating Position	Base Up or Down
Power Factor	0.9
SDS Class	LED_Lamp
Product Technology	LED
Fluor Equiv	42W
Incandescent Equivalent	100W

### ELECTRICAL

CCT (Kelvin Temp)	5000K
Hours Rated	50000
Beam Angle (degree)	110
Color Temp	Natural Light
CRI	80+
Operating Temp	-4F to +113F (-20C to +45C)
Lumens	1850L
Volts	Ballast Dependent
Watts	16W

### PHYSICAL

Lamp Base	G24q (4-Pin)
Finish	Frost
Housing Color	White
ANSI Base	G24q
Lamp Type	PL
MOD Lamps	3.75
MOL	5.19

### ADDITIONAL INFO

Warranty	5-Years
Rated For Enclosed Fixture	Yes

### PACKAGING

UPC	045923224072
Case Cube	1.5156
Case Height	14.17
Case Length	20.86
Case Quantity	20
Case UPC	10045923224079
Case Weight	11.68
Case Width	8.86
EA Cube	0.0543
EA Height	6.3
EA Length	3.86
EA Quantity	1
EA Weight	0.33
EA Width	3.86
Inner Cube	0.6439
Inner Height	6.7
Inner Length	20.08
Inner Quantity	10
Inner UPC	20045923224076
Inner Weight	5.5
Inner Width	8.27
Pack Type	Box
Web Length	5.19
Web Width	3.75

### COMPLIANCE

DLC ID	PL9E574BZGHJ
FCC Compliant	Yes
Location Rating	Damp
NSF Approved	Yes
ROHS Compliant	Yes
Safety Listing	cULus
California Ban	Lawful for sale
DLC Approved	Yes
Title 20	Exempt