SATCO | NUVO



Project / Job Name:

Location:

Fixture Type:

Notes:

S21429 - 7 Watt; PL LED; G24D Base; Frost Finish; Type A/B Dual Ballast; 5000K; 120-277 Range Voltage

GENERAL

Company	SATCO
EA Height	4.72
EA Width	1.77
EA Length	1.77
Lamp Ballast Type AB	Type A/B
Ballasting Requirements	Ballast required (Type A) or Ballast Bypass (Type B)
Lamp Filament	LED
Material	Aluminum
Fixture Type	PL
Status	Active
Surge Protection	Built-in-surge protection - 0.5KV
CCT Selectable	No
Wattage Selectable	No
Finish Family	White
Amps	0.058-0.025A
Has Camera	No
IOT Enabled	No
Lens Finish	Frosted
Lens Material	Polycarbonate (PC)
Minimum Compartment Size	Length 6.10 in. Width 6.10 in. Height: 7.87 in.
Operating Position	Universal
Power Factor	0.9
SDS Class	LED_Lamp
Indoor Outdoor	Indoor
Product Technology	LED
Fluor Equiv	13W/18W/26W
Serviceable Battery	No
Battery Indicator	No
Digital Display	No

ELECTRICAL

CCT (Kelvin Temp)	5000K
Dimmable	Non-Dimmable
Hours Rated	50000
Beam Angle (degree)	300
Color Temp	Natural Light
CRI	80+
Operating Frequency	50/60Hz
Operating Temp	-4F to +113F (-20C to +45C)
Lumens	910L
Volts	120V-277V
Watts	7W

PHYSICAL

Lamp Base	G24d (2-Pin)
Finish	Frost
Housing Color	White
ANSI Base	G24d
Lamp Type	PL
MOD Lamps	1.52
MOL	4.53

ADDITIONAL INFO

Warranty	5-Years
Rated For Enclosed Fixture	Yes

PACKAGING

UPC	045923409448
Case Cube	0.3497
Case Height	4.92
Case Length	11.73
Case Quantity	24
Case UPC	10045923409445
Case Weight	5.33
Case Width	10.47
EA Cube	0.0086
EA Height	4.72
EA Length	1.77
EA Quantity	1
EA Weight	0.17
EA Width	1.77
Inner Cube	0.0619
Inner Height	3.94
Inner Length	5.47
Inner Quantity	6
Inner UPC	20045923409442
Inner Weight	1.22
Inner Width	4.96
Pack Type	Box
Web Length	4.53
Web Width	1.52

COMPLIANCE

FCC Compliant	Yes
Location Rating	Damp
NSF Approved	Yes
ROHS Compliant	Yes
Safety Listing	cULus - Classified, cULus - Listed
California Ban	Lawful for sale
DLC Approved	No
Title 20	Exempt
T24/JA8 Compliant	No

© Satco Products, Inc.
All rights reserved 2026