



Project / Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**S21709** - 4.5 Watt B11 LED Filament; Clear; Medium base; 2700K; 350 Lumens; 120 Volt; 3-Pack



### GENERAL

|                         |                                |
|-------------------------|--------------------------------|
| Company                 | SATCO                          |
| EA Height               | 4.33                           |
| EA Width                | 1.57                           |
| EA Length               | 4.72                           |
| Dimmable Text           | Forward Phase or Reverse Phase |
| Lamp Filament           | LED Filament                   |
| Fixture Type            | Candle                         |
| Status                  | Discontinued                   |
| CCT Selectable          | No                             |
| Wattage Selectable      | No                             |
| Finish Family           | No Finish                      |
| Amps                    | 0.038A                         |
| Has Camera              | No                             |
| IOT Enabled             | No                             |
| Lens Finish             | Clear                          |
| Lensed                  | Yes                            |
| Operating Position      | Universal                      |
| Power Factor            | 1                              |
| SDS Class               | LED_Lamp                       |
| Product Technology      | LED                            |
| Incandescent Equivalent | 40W                            |

### ELECTRICAL

|                     |                            |
|---------------------|----------------------------|
| CCT (Kelvin Temp)   | 2700K                      |
| Dimmable            | Yes-Dimmable               |
| Hours Rated         | 15000                      |
| Beam Angle (degree) | 360                        |
| Color Temp          | Warm White                 |
| CRI                 | 80+                        |
| Dimming Type        | 120V only, Phase cut       |
| Operating Temp      | -20C (-4F) to +45C (+113F) |
| Lumens              | 350L                       |
| Volts               | 120v                       |
| Watts               | 4.5W                       |

### PHYSICAL

|           |        |
|-----------|--------|
| Lamp Base | Medium |
| Finish    | Clear  |
| ANSI Base | E26    |
| Lamp Type | B11    |
| MOD Lamps | 1.38   |
| MOL       | 3.88   |

### ADDITIONAL INFO

|                            |         |
|----------------------------|---------|
| Warranty                   | 2-Years |
| Rated For Enclosed Fixture | Yes     |

### PACKAGING

|                |                |
|----------------|----------------|
| UPC            | 045923217098   |
| Case Cube      | 0.3086         |
| Case Height    | 9.45           |
| Case Length    | 10.24          |
| Case Quantity  | 12             |
| Case UPC       | 10045923217095 |
| Case Weight    | 3.31           |
| Case Width     | 5.51           |
| EA Cube        | 0.0186         |
| EA Height      | 4.33           |
| EA Length      | 4.72           |
| EA Quantity    | 1              |
| EA Weight      | 0.26           |
| EA Width       | 1.57           |
| Inner Cube     | 0.0            |
| Inner Height   | 0.0            |
| Inner Length   | 0.0            |
| Inner Quantity | 0              |
| Inner Weight   | 0.0            |
| Inner Width    | 0.0            |
| Pack Type      | Box            |
| Web Length     | 3.88           |
| Web Width      | 1.38           |

### COMPLIANCE

|                 |               |
|-----------------|---------------|
| FCC Compliant   | Yes           |
| Location Rating | Damp          |
| ROHS Compliant  | Yes           |
| Safety Listing  | cULus         |
| California Ban  | Non-Compliant |
| DLC Approved    | No            |
| Title 20        | No            |
| T24 Compliant   | No            |
| US State Ban    | CA            |