



Project / Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**S21861** - 4 Watt T6.5 LED Filament; Clear; Bayonet Double Contact Base; 3000K; 400 Lumens; 120 Volt



### GENERAL

|                         |   |
|-------------------------|---|
| Company                 | SATCO   |
| EA Height               | 8.54  |
| EA Width                | 4.96  |
| EA Length               | 1.34  |
| Dimmable Text           | Forward Phase or Reverse Phase or Phase Selectable; 120V only |
| Lamp Filament           | LED Filament  |
| Material                | Glass / Copper  |
| Fixture Type            | Tubular   |
| Status                  | Active  |
| Style                   | Traditional   |
| CCT Selectable          | No  |
| Wattage Selectable      | No  |
| Finish Family           | Clear   |
| Amps                    | 0.033A  |
| Has Camera              | No  |
| IOT Enabled             | No  |
| Operating Position      | Universal   |
| Power Factor            | 0.76  |
| SDS Class               | LED_Lamp  |
| Indoor Outdoor          | Indoor, Outdoor   |
| Product Technology      | LED   |
| Incandescent Equivalent | 40W   |

### ELECTRICAL

|                     |                            |
|---------------------|----------------------------|
| CCT (Kelvin Temp)   | 3000K                      |
| Dimmable            | Yes-Dimmable               |
| Hours Rated         | 15000                      |
| Beam Angle (degree) | 300                        |
| Color Temp          | Soft White                 |
| CRI                 | 90+                        |
| Dimming Type        | 120V only, Phase cut       |
| Operating Frequency | 60Hz                       |
| Operating Temp      | -20C (-4F) to +45C (+113F) |
| Lumens              | 400L                       |
| Volts               | 120v                       |
| Watts               | 4W                         |

### PHYSICAL

|               |                        |
|---------------|------------------------|
| Lamp Base     | Bayonet Double Contact |
| Finish        | Clear                  |
| Housing Color | None                   |
| ANSI Base     | BA15d                  |
| Lamp Type     | T6.5                   |
| MOD Lamps     | 0.79                   |
| MOL           | 5.0                    |

### ADDITIONAL INFO

|                            |                                      |
|----------------------------|--------------------------------------|
| Warranty                   | 2-Years                              |
| Installation Notes         | Not for use in vapor tight fixtures. |
| Rated For Enclosed Fixture | Yes                                  |

### PACKAGING

|                |                |
|----------------|----------------|
| UPC            | 045923218613   |
| Case Cube      | 1.0647         |
| Case Height    | 19.37          |
| Case Length    | 8.07           |
| Case Quantity  | 24             |
| Case UPC       | 10045923218610 |
| Case Weight    | 4.1            |
| Case Width     | 11.77          |
| EA Cube        | 0.0328         |
| EA Height      | 8.54           |
| EA Length      | 1.34           |
| EA Quantity    | 1              |
| EA Weight      | 0.11           |
| EA Width       | 4.96           |
| Inner Cube     | 0.5107         |
| Inner Height   | 11.61          |
| Inner Length   | 7.91           |
| Inner Quantity | 12             |
| Inner UPC      | 20045923218617 |
| Inner Weight   | 1.72           |
| Inner Width    | 9.61           |
| Pack Type      | Carded         |
| Web Length     | 5.0            |
| Web Width      | 0.79           |

### COMPLIANCE

|                 |                   |
|-----------------|-------------------|
| FCC Compliant   | Yes               |
| Location Rating | Wet               |
| ROHS Compliant  | Yes               |
| Safety Listing  | cETLus - Listed   |
| California Ban  | Lawful for sale   |
| UL Application  | Filament LED Lamp |
| DLC Approved    | No                |
| Title 20        | Exempt            |
| T24 Compliant   | No                |