



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S22211 - 5.5 Watt PAR20 LED; 90 CRI; 4000K; 40 deg. Beam Angle; Medium base; 120 Volt



GENERAL

Company	SATCO
EA Height	3.5
EA Width	2.64
EA Length	2.64
Candle Power	50.0
Dimmable Text	Forward Phase
Lamp Filament	LED
Material	Aluminum / Plastic
Fixture Type	PAR
Status	Active
Style	Utility
CCT Selectable	No
Wattage Selectable	No
Finish Family	No Finish
Amps	0.046A
Has Camera	No
IOT Enabled	No
Lens Finish	Clear
Lens Material	Plastic (PS)
Lensed	Yes
Operating Position	Universal
Power Factor	0.7
SDS Class	LED_Lamp
Indoor Outdoor	Indoor, Outdoor
Product Technology	LED
Incandescent Equivalent	50W

ELECTRICAL

CCT (Kelvin Temp)	4000K
Dimmable	Yes-Dimmable
Hours Rated	15000
Beam Angle (degree)	40
Color Temp	Cool White
CRI	90+
Dimming Type	120V only, Phase cut
Operating Frequency	60Hz
Operating Temp	-20C (-4F) to +45C (+113F)
Lumens	500L
Volts	120v
Watts	5.5W

PHYSICAL

Lamp Base	Medium
Finish	Clear
Housing Color	White
ANSI Base	E26
Lamp Type	PAR20
MOD Lamps	2.48
MOL	3.19

ADDITIONAL INFO

Warranty	2-Years
Rated For Enclosed Fixture	Yes

PACKAGING

UPC	045923210440
Case Cube	0.5747
Case Height	4.72
Case Length	17.52
Case Quantity	24
Case UPC	10045923210447
Case Weight	6.93
Case Width	12.01
EA Cube	0.0141
EA Height	3.5
EA Length	2.64
EA Quantity	1
EA Weight	0.15
EA Width	2.64
Inner Cube	0.1101
Inner Height	3.94
Inner Length	8.46
Inner Quantity	6
Inner UPC	20045923210444
Inner Weight	0.99
Inner Width	5.71
Pack Type	Color Box
Web Length	3.19
Web Width	2.48

COMPLIANCE

FCC Compliant	Yes
Location Rating	Wet
ROHS Compliant	Yes
Safety Listing	cULus - Certified, cULus - Listed
California Ban	Lawful for sale
DLC Approved	No
Title 20	Yes
T24 Compliant	No