



Project / Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**S22214 - 8.5 Watt PAR30L LED; 90 CRI; 3000K; 40 deg. Beam Angle; Medium base; 120 Volt**



**GENERAL**

Company	SATCO
EA Height	4.8
EA Width	3.9
EA Length	3.9
Candle Power	75.0
Dimmable Text	Forward Phase or Reverse Phase or Adaptive Phase
Lamp Filament	LED
Material	Aluminum / Plastic
Fixture Type	PAR
Status	Active
Style	Utility
CCT Selectable	No
Wattage Selectable	No
Finish Family	No Finish
Amps	0.071A
Has Camera	No
IOT Enabled	No
Lens Finish	Clear
Lens Material	Plastic (PS)
Lensed	Yes
Operating Position	Universal
Power Factor	0.7
SDS Class	LED_Lamp
Indoor Outdoor	Indoor, Outdoor
Product Technology	LED
Incandescent Equivalent	75W

**ELECTRICAL**

CCT (Kelvin Temp)	3000K
Dimmable	Yes-Dimmable
Hours Rated	15000
Beam Angle (degree)	40
Color Temp	Soft White
CRI	90+
Dimming Type	120V only, Phase cut
Operating Frequency	60Hz
Operating Temp	-20C (-4F) to +45C (+113F)
Lumens	700L
Volts	120v
Watts	8.5W

**PHYSICAL**

Lamp Base	Medium
Finish	Clear
Housing Color	White
ANSI Base	E26
Lamp Type	PAR30LN
MOD Lamps	3.74
MOL	4.41

**ADDITIONAL INFO**

Warranty	2-Years
Rated For Enclosed Fixture	Yes

**PACKAGING**

UPC	045923210471
Case Cube	0.7499
Case Height	5.91
Case Length	17.13
Case Quantity	12
Case UPC	10045923210478
Case Weight	7.35
Case Width	12.8
EA Cube	0.0422
EA Height	4.8
EA Length	3.9
EA Quantity	1
EA Weight	0.29
EA Width	3.9
Inner Cube	0.2989
Inner Height	5.12
Inner Length	12.2
Inner Quantity	6
Inner UPC	20045923210475
Inner Weight	1.98
Inner Width	8.27
Pack Type	Color Box
Web Length	4.41
Web Width	3.74

**COMPLIANCE**

FCC Compliant	Yes
Location Rating	Wet
ROHS Compliant	Yes
Safety Listing	cULus - Certified, cULus - Listed
California Ban	Lawful for sale
DLC Approved	No
Title 20	Yes
T24 Compliant	No