



Project / Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**S2231** - 39 Watt; Halogen; PAR20; Clear; 1500 Average rated hours; 530 Lumens; Medium base; 120 Volt



**GENERAL**

|                          |                       |
|--------------------------|-----------------------|
| Company                  | SATCO                 |
| EA Height                | 3.25                  |
| EA Width                 | 2.5                   |
| EA Length                | 2.5                   |
| Center Beam Candle Power | 2500                  |
| Lamp Filament            | CC-8                  |
| Fixture Type             | PAR                   |
| Spot Type                | NSP - Narrow Spot     |
| Status                   | Obsolete              |
| CCT Selectable           | No                    |
| Wattage Selectable       | No                    |
| Finish Family            | No Finish             |
| Amps                     | 0.325A                |
| Has Camera               | No                    |
| IOT Enabled              | No                    |
| Lens Finish              | Clear                 |
| Lensed                   | Yes                   |
| Operating Position       | Universal             |
| SDS Class                | Halogen_Tungsten_Lamp |
| Product Technology       | Halogen               |
| Incandescent Equivalent  | 50W                   |

**ELECTRICAL**

|                     |              |
|---------------------|--------------|
| CCT (Kelvin Temp)   | 2900K        |
| Dimmable            | Yes-Dimmable |
| Hours Rated         | 1500         |
| Beam Angle (degree) | 10           |
| Color Temp          | Warm White   |
| CRI                 | 100          |
| Lumens              | 530L         |
| Volts               | 120v         |
| Watts               | 39W          |

**PHYSICAL**

|           |        |
|-----------|--------|
| Lamp Base | Medium |
| Finish    | Clear  |
| ANSI Base | E26    |
| Lamp Type | PAR20  |
| MOD Lamps | 2.5    |
| MOL       | 3.125  |

**PACKAGING**

|               |                |
|---------------|----------------|
| UPC           | 045923022319   |
| Case Cube     | 0.235          |
| Case Height   | 3.94           |
| Case Length   | 13.08          |
| Case Quantity | 15             |
| Case UPC      | 10045923022316 |
| Case Weight   | 3.75           |
| Case Width    | 7.88           |
| EA Cube       | 0.0118         |
| EA Height     | 3.25           |
| EA Length     | 2.5            |
| EA Quantity   | 1              |
| EA Weight     | 0.23           |
| EA Width      | 2.5            |
| Pack Type     | Box            |
| Web Length    | 3.125          |
| Web Width     | 2.5            |

**COMPLIANCE**

|                             |                |
|-----------------------------|----------------|
| CA T20 Compliant Substitute | S9485          |
| Location Rating             | Damp           |
| MA Alt Sub                  | S29401         |
| NV Alt Sub                  | S29401         |
| ROHS Compliant              | Yes            |
| Safety Listing              | Not Applicable |
| California Ban              | Non-Compliant  |
| DLC Approved                | No             |
| Title 20                    | No             |
| T24 Compliant               | No             |
| US State Ban                | CA, MA, NV     |