SATCO | NUVO



Project / Job Name:

Location:

Fixture Type:

Notes:

**S23164** - 36 Watt LED HID Replacement; CCT Selectable; Type B; Ballast Bypass; Mogul Extended Base; 277-480 Volt; ColorQuick Technology

DAMP LOCATION · DIMMABLE · ENCLOSED FIXTURE · CLASSIFIED cULus · FC · RoHS COMPLIANT · CCT SELECTABLE · 50,000 HOURS · TYPE B · 5 YEAR WARRANTY

## GENERAL

| | |
|---|---|
| Company | SATCO |
| EA Height | 3.66 |
| EA Width | 3.66 |
| EA Length | 9.8 |
| Lamp Ballast Type AB | Type B |
| Ballasting Requirements | Ballast Bypass |
| Lamp Filament | LED |
| Material | Aluminum / Polycarbonate (PC) |
| Fixture Type | Corncob |
| Status | Active |
| Style | Utility |
| Surge Protection | Built-in surge protection - 4KV |
| Total Harmonic Distortion | 5.90% |
| CCT Selectable | Yes |
| Wattage Selectable | No |
| Finish Family | White |
| Amps | 0.130-0.075A |
| IOT Enabled | No |
| Lens Finish | Clear |
| Lens Material | Plastic |
| Lensed | Yes |
| Operating Position | Universal |
| Photo Cell | Optional |
| Power Factor | 0.9 |
| SDS Class | LED_Lamp |
| Indoor Outdoor | Indoor, Outdoor |
| Product Technology | LED |
| Incandescent Equivalent | 125W |
| Serviceable Battery | No |
| Battery Indicator | No |
| Digital Display | No |

## ELECTRICAL

| | |
|---|---|
| CCT (Kelvin Temp) | 3000K/4000K/5000K |
| Dimmable | Yes-Dimmable |
| Hours Rated | 50000 |
| Beam Angle (degree) | 300 |
| Color Temp | Warm to Cool White |
| CRI | 80+ |
| Dimming Type | Only dimmable via WiFi Module 80-954 (available for purchase) and via the Starfish App, Smart-Starfish App through Wifi Module only |
| Operating Frequency | 50/60Hz |
| Operating Temp | -22F to +113F (-30C to +45C) |
| HID Equivalent | 175W |
| Lumens | 4680L/5040L/4860L |
| Volts | 277V-480V |
| Watts | 36W |
| Max Lumens | 5040L |

## PHYSICAL

| | |
|---|---|
| Lamp Base | Mogul Extended |
| Finish | WHITE |
| Housing Color | Dark Gray |
| ANSI Base | EX39 |
| Lamp Type | Corncob |
| MOD Lamps | 3.35 |
| MOL | 8.35 |

## ADDITIONAL INFO

| | |
|---|---|
| Warranty | 5-Years |
| Installation Notes | Not for use in vapor tight fixtures. |
| Rated For Enclosed Fixture | Yes |

## PACKAGING

| | |
|---|---|
| UPC | 045923231698 |
| Case Cube | 1.0689 |
| Case Height | 10.4 |
| Case Length | 15.35 |
| Case Quantity | 12 |
| Case UPC | 10045923231695 |
| Case Weight | 22.06 |
| Case Width | 11.57 |
| EA Cube | 0.076 |
| EA Height | 3.66 |
| EA Length | 9.8 |
| EA Quantity | 1 |
| EA Weight | 1.65 |
| EA Width | 3.66 |
| Pack Type | Box |
| Web Length | 8.35 |
| Web Width | 3.35 |

## COMPLIANCE

| | |
|---|---|
| DLC ID | S-V389PR |
| FCC Compliant | Yes |
| IP Rating | IP64 |
| Location Rating | Damp |
| NSF Approved | No |
| ROHS Compliant | Yes |
| Safety Listing | cRUus - Recognized Component, cULus - Certified, cULus - Classified |
| California Ban | Lawful for sale |
| DLC Approved | Yes |
| Title 20 | Exempt |
| T24/JA8 Compliant | No |



© Satco Products, Inc.
All rights reserved 2026