



Project / Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**S2840** - 40 Watt A15 Incandescent; Clear; Appliance Lamp; 2500 Average rated hours; 300/225 Lumens; Medium base; 130/120 Volt; Teflon/PFA Shatterproof



GENERAL	
Company	SATCO
EA Height	3.54
EA Width	1.93
EA Length	1.93
Lamp Filament	C-9/4
Fixture Type	Type A
Status	Active
CCT Selectable	No
Wattage Selectable	No
Finish Family	Clear
Additional Info	300 Lumens at 130V; 225 Lumens at 120V
Amps	0.308-0.333A
Has Camera	No
IOT Enabled	No
Lens Finish	Clear
Lensed	Yes
Operating Position	Universal
SDS Class	Incandescent_Lamp
Shatter Proof Type	Teflon/PFA Shatterproof
Product Technology	Incandescent

ELECTRICAL	
CCT (Kelvin Temp)	2700K
Dimmable	Yes-Dimmable
Hours Rated	2500
Beam Angle (degree)	360
Color Temp	Warm White
CRI	100
Lumens	300L/225L
Volts	130V/120V
Watts	40W

PHYSICAL	
Lamp Base	Medium
Finish	Clear
Housing Color	None
ANSI Base	E26
Lamp Type	A15
MOD Lamps	1.88
MOL	3.5

ADDITIONAL INFO	
Installation Notes	Shatterproof coated incandescent lamps should not be used in close proximity to live poultry or birds

PACKAGING	
UPC	045923028403
Case Cube	5.5202
Case Height	21.63
Case Length	21.0
Case Quantity	500
Case UPC	10045923028400
Case Weight	49.13
Case Width	21.0
EA Cube	0.0076
EA Height	3.54
EA Length	1.93
EA Quantity	1
EA Weight	0.1
EA Width	1.93
Inner Cube	0.2432
Inner Height	4.0
Inner Length	10.25
Inner Quantity	25
Inner UPC	20045923028407
Inner Weight	1.95
Inner Width	10.25
Pack Type	Box
Web Length	3.5
Web Width	1.88

COMPLIANCE	
CA Prop 65	Lead, PFAS
ROHS Compliant	Yes
Safety Listing	Not Applicable
California Ban	Lawful for sale
DLC Approved	No
Title 20	Exempt
T24/JA8 Compliant	No