



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S28730 - 6 Watt LED PL 2-PIN; GX23 Base;
27K/30K/35K/40K/50K CCT Selectable; 120-277 Volt;
Type B; Ballast Bypass



GENERAL

Company	SATCO
EA Height	7.4
EA Width	0.98
EA Length	1.46
Lamp Ballast Type AB	Type B
Ballasting Requirements	Ballast Bypass
Lamp Filament	LED
Material	Polycarbonate (PC)
Fixture Type	Miniature
Status	Discontinued
Style	Transitional
Surge Protection	Built-in surge protection - 1.5KV
Total Harmonic Distortion	<20%
CCT Selectable	Yes
Wattage Selectable	No
Finish Family	White
Amps	0.050A-0.022A
Has Camera	No
IOT Enabled	No
Operating Position	Universal
Power Factor	0.9
SDS Class	LED_Lamp
Indoor Outdoor	Indoor
Product Technology	LED
Fluor Equiv	13W

ELECTRICAL

CCT (Kelvin Temp)	2700K/3000K/3500K/4000K/5000K
Dimmable	Non-Dimmable
Hours Rated	50000
Beam Angle (degree)	360
Color Temp	Warm White to Natural Light
CRI	80+
Operating Frequency	50/60Hz
Operating Temp	-4F to +113F (-20C to +45C)
Lumens	600L/625L/650L/650L/625L
Volts	120V-277V
Watts	6W

PHYSICAL

Lamp Base	GX23 (2-Pin)
Finish	Frost
Housing Color	White
ANSI Base	GX23
Lamp Type	PL
MOD Lamps	1.27
MOL	7.09

ADDITIONAL INFO

Warranty	5-Years
Rated For Enclosed Fixture	Yes

PACKAGING

UPC	045923287305
Case Cube	0.5617
Case Height	8.98
Case Length	17.72
Case Quantity	50
Case UPC	10045923287302
Case Weight	8.82
Case Width	6.1
EA Cube	0.0061
EA Height	7.4
EA Length	1.46
EA Quantity	1
EA Weight	0.15
EA Width	0.98
Inner Cube	0.0813
Inner Height	7.99
Inner Length	5.31
Inner Quantity	10
Inner UPC	20045923287309
Inner Weight	1.75
Inner Width	3.31
Pack Type	Box
Web Length	7.09
Web Width	1.27

COMPLIANCE

FCC Compliant	Yes
Location Rating	Damp
NSF Approved	No
ROHS Compliant	Yes
Safety Listing	cETLus - Classified
California Ban	Lawful for sale
DLC Approved	No
Title 20	Exempt
T24/JA8 Compliant	No