



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S28980 - 10/20/30 Wattage Selectable; LED Hi-Pro Wall Pack; CCT Selectable 3K/4K/5K; Type B; Ballast Bypass; Medium base; 100-277 Volt; ColorQuick Technology; PowerQuick Technology



GENERAL

Company	SATCO
EA Height	4.02
EA Width	4.02
EA Length	9.37
Lamp Ballast Type AB	Type B
Ballasting Requirements	Ballast Bypass
Dimmable Text	Dimmable only via the wattage/lumen selectable dial included on lamp
Lamp Filament	LED
Material	Aluminum / Plastic
Fixture Type	Corncob
Status	Active
Style	Contemporary
Surge Protection	Built-in surge protection - 4KV
CCT Selectable	Yes
Wattage Selectable	Yes
Finish Family	White
Amps	0.100-0.0361/0.200-0.072/0.300-0.108A
Has Camera	No
IOT Enabled	No
Lens Material	Plastic
Minimum Compartment Size	Length: 8 in. Width: 8 in. Height: 11 in.
Operating Position	Horizontal
Power Factor	>0.9
SDS Class	LED_Lamp
Indoor Outdoor	Indoor, Outdoor
Product Technology	LED
Incandescent Equivalent	50W-70W

ELECTRICAL

CCT (Kelvin Temp)	3000K/4000K/5000K
Dimmable	Yes-Dimmable
Hours Rated	50000
Beam Angle (degree)	180
Color Temp	Warm to Cool White
CRI	80+
Dimming Type	Dimmable only via the wattage/lumen selectable dial included on lamp
Operating Frequency	50-60Hz
Operating Temp	-30C (-22F) to +45C (+113F)
HID Equivalent	150W-175W
Lumens	1700L/3200L/4500L
Volts	120V-277V
Watts	10W/20W/30W

PHYSICAL

Lamp Base	Medium
Finish	WHITE
Housing Color	White
ANSI Base	E26
Lamp Type	Corncob
MOD Lamps	3.62
MOL	7.0

ADDITIONAL INFO

Warranty	5-Years
Installation Notes	Not for use in vapor tight fixtures.
Rated For Enclosed Fixture	Yes

PACKAGING

UPC	045923289804
Case Cube	1.4584
Case Height	10.74
Case Length	17.63
Case Quantity	12
Case UPC	10045923289801
Case Weight	23.21
Case Width	13.31
EA Cube	0.0876
EA Height	4.02
EA Length	9.37
EA Quantity	1
EA Weight	1.77
EA Width	4.02
Inner Cube	0.6149
Inner Height	9.96
Inner Length	12.67
Inner Quantity	6
Inner UPC	20045923289808
Inner Weight	11.14
Inner Width	8.42
Pack Type	Box
Web Length	7.0
Web Width	3.62

COMPLIANCE

Bug Rating	B2-U3-G2
FCC Compliant	Yes
IP Rating	IP64
Location Rating	Damp
NSF Approved	No
ROHS Compliant	Yes
Safety Listing	cULus - Certified, cULus - Classified, cULus - Listed
California Ban	Lawful for sale
DLC Approved	No
Title 20	Exempt
T24 Compliant	No