



Project / Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**S2908** - 4 Watt; T5; Preheat Fluorescent; 6500K  
Daylight; 75 CRI; Miniature Bi Pin base



**GENERAL**

Company	SATCO
EA Height	0.63
EA Width	0.63
EA Length	6.02
Lamp Ballast Type AB	Type A
Ballasting Requirements	For Use With Preheat Ballast
Fixture Type	Linear
Hg Content	5.0
Status	Obsolete
CCT Selectable	No
Wattage Selectable	No
Finish Family	White
Has Camera	No
IOT Enabled	No
Lens Finish	Frost
Lensed	Yes
Nominal Length	6.0
Operating Position	Universal
SDS Class	Linear_Fluorescent_Lamp
Product Technology	Fluorescent

**ELECTRICAL**

CCT (Kelvin Temp)	6500K
Dimmable	Non-Dimmable
Hours Rated	5000
Beam Angle (degree)	360
Color Temp	Daylight
CRI	75+
Operating Temp	Ballast Dependent
Lumens	115L
Watts	4W

**PHYSICAL**

Lamp Base	Miniature Bi Pin
Finish	Frost
Housing Color	None
ANSI Base	G5
Lamp Type	T5
MOD Lamps	0.63
MOL	5.91

**ADDITIONAL INFO**

Warranty	3-Years
----------	---------

**PACKAGING**

UPC	045923029080
Case Cube	1.322
Case Height	15.96
Case Length	19.11
Case Quantity	500
Case UPC	10045923029087
Case Weight	17.64
Case Width	7.49
EA Cube	0.0014
EA Height	0.63
EA Length	6.02
EA Quantity	1
EA Weight	0.04
EA Width	0.63
Inner Cube	0.0202
Inner Height	1.38
Inner Length	6.9
Inner Quantity	10
Inner UPC	20045923029084
Inner Weight	0.34
Inner Width	3.66
Pack Type	Sleeve
Web Length	5.91
Web Width	0.63

**COMPLIANCE**

Location Rating	Damp
ROHS Compliant	Yes
Safety Listing	Not Applicable
California Ban	Non-Compliant
DLC Approved	No
Title 20	No
T24/JA8 Compliant	No
US State Ban	CA, CO, HI, ME, MN, OR, RI, VT