



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S2911 - 13 Watt; T5; Preheat Fluorescent; 6500K
Daylight; 76 CRI; Miniature Bi Pin base



GENERAL

Company	SATCO
EA Height	0.63
EA Width	0.63
EA Length	20.94
Lamp Ballast Type AB	Type A
Ballasting Requirements	For Use With Preheat Ballast
Fixture Type	Linear
Hg Content	5.0
Status	Active
CCT Selectable	No
Wattage Selectable	No
Finish Family	White
Has Camera	No
IOT Enabled	No
Lens Finish	Frost
Lensed	Yes
Nominal Length	21.0
Operating Position	Universal
SDS Class	Linear_Fluorescent_Lamp
Product Technology	Fluorescent

ELECTRICAL

CCT (Kelvin Temp)	6500K
Dimmable	Non-Dimmable
Hours Rated	5000
Beam Angle (degree)	360
Color Temp	Daylight
CRI	75+
Operating Temp	Ballast Dependent
Lumens	780L
Watts	13W

PHYSICAL

Lamp Base	Miniature Bi Pin
Finish	Frost
Housing Color	None
ANSI Base	G5
Lamp Type	T5
MOD Lamps	0.63
MOL	20.91

ADDITIONAL INFO

Warranty	3-Years
----------	---------

PACKAGING

UPC	045923029110
Case Cube	1.8005
Case Height	16.75
Case Length	22.46
Case Quantity	200
Case UPC	10045923029117
Case Weight	28.22
Case Width	8.27
EA Cube	0.0048
EA Height	0.63
EA Length	20.94
EA Quantity	1
EA Weight	0.13
EA Width	0.63
Inner Cube	0.0674
Inner Height	21.79
Inner Length	3.66
Inner Quantity	10
Inner UPC	20045923029114
Inner Weight	1.39
Inner Width	1.46
Pack Type	Sleeve
Web Length	20.91
Web Width	0.63

COMPLIANCE

CA Prop 65	Lead
Location Rating	Damp
ROHS Compliant	Yes
Safety Listing	Not Applicable
California Ban	Non-Compliant
DLC Approved	No
Title 20	No
T24 Compliant	No
US State Ban	CA, CO, HI, ME, MN, OR, RI, VT