



Project / Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**S29425** - 12.5 Watt; PAR30LN LED; 2700K; 25 deg. Beam Angle; Medium base; 120 Volt



**GENERAL**

|                          |  |
|--------------------------|--|
| Company                  | SATCO  |
| EA Height                | 4.92   |
| EA Width                 | 3.94   |
| EA Length                | 3.94   |
| Center Beam Candle Power | 2910   |
| Dimmable Text            | Forward Phase or Reverse Phase or Phase Selectable |
| Lamp Filament            | LED  |
| Material                 | Plastic  |
| Fixture Type             | PAR  |
| Status                   | Active   |
| Style                    | Utility  |
| CCT Selectable           | No   |
| Wattage Selectable       | No   |
| Finish Family            | No Finish  |
| Amps                     | 0.104A   |
| Has Camera               | No   |
| IOT Enabled              | No   |
| Lens Finish              | Clear  |
| Lens Material            | Thermo Plastic (PBT)                               |
| Lensed                   | Yes  |
| Operating Position       | Universal  |
| Photo Cell               | No   |
| Power Factor             | 0.9  |
| SDS Class                | LED_Lamp   |
| Indoor Outdoor           | Indoor, Outdoor                                    |
| Product Technology       | LED  |
| Fluor Equiv              | 15W  |
| Incandescent Equivalent  | 75W  |

**ELECTRICAL**

|                     |                            |
|---------------------|----------------------------|
| CCT (Kelvin Temp)   | 2700K                      |
| Dimmable            | Yes-Dimmable               |
| Hours Rated         | 25000                      |
| Beam Angle (degree) | 25                         |
| Color Temp          | Warm White                 |
| CRI                 | 90+                        |
| Dimming Type        | 120V only, Phase cut       |
| Operating Frequency | 60Hz                       |
| Operating Temp      | -20C (-4F) to +45C (+113F) |
| Lumens              | 1000L                      |
| Volts               | 120v                       |
| Watts               | 12.5W                      |

**PHYSICAL**

|               |         |
|---------------|---------|
| Lamp Base     | Medium  |
| Finish        | Clear   |
| Housing Color | Silver  |
| ANSI Base     | E26     |
| Lamp Type     | PAR30LN |
| MOD Lamps     | 3.74    |
| MOL           | 4.57    |

**ADDITIONAL INFO**

|                            |         |
|----------------------------|---------|
| Warranty                   | 5-Years |
| Rated For Enclosed Fixture | Yes     |

**PACKAGING**

|                |                |
|----------------|----------------|
| UPC            | 045923294259   |
| Case Cube      | 0.8425         |
| Case Height    | 17.52          |
| Case Length    | 6.3            |
| Case Quantity  | 12             |
| Case UPC       | 10045923294256 |
| Case Weight    | 6.22           |
| Case Width     | 13.19          |
| EA Cube        | 0.0442         |
| EA Height      | 4.92           |
| EA Length      | 3.94           |
| EA Quantity    | 1              |
| EA Weight      | 0.35           |
| EA Width       | 3.94           |
| Inner Cube     | 0.3228         |
| Inner Height   | 12.52          |
| Inner Length   | 5.31           |
| Inner Quantity | 6              |
| Inner UPC      | 20045923294253 |
| Inner Weight   | 2.56           |
| Inner Width    | 8.39           |
| Pack Type      | Box            |
| Web Length     | 4.57           |
| Web Width      | 3.74           |

**COMPLIANCE**

|                 |                       |
|-----------------|-----------------------|
| FCC Compliant   | Yes                   |
| Location Rating | Wet                   |
| ROHS Compliant  | Yes                   |
| Safety Listing  | cULus - Listed        |
| California Ban  | California T24 Listed |
| DLC Approved    | No                    |
| Title 20        | Yes                   |
| T24 Compliant   | Yes                   |