



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S29429 - 12.5 Watt; PAR30LN LED; 5000K; 25 deg. Beam Angle; Medium base; 120 Volt



GENERAL

Company	SATCO
EA Height	4.92
EA Width	3.94
EA Length	3.94
Center Beam Candle Power	2910
Dimmable Text	Forward Phase or Reverse Phase or Phase Selectable
Lamp Filament	LED
Material	Plastic
Fixture Type	PAR
Status	Active
Style	Utility
CCT Selectable	No
Wattage Selectable	No
Finish Family	No Finish
Amps	0.104A
Has Camera	No
IOT Enabled	No
Lens Finish	Clear
Lens Material	Thermo Plastic (PBT)
Lensed	Yes
Operating Position	Universal
Photo Cell	No
Power Factor	0.9
SDS Class	LED_Lamp
Indoor Outdoor	Indoor, Outdoor
Product Technology	LED
Fluor Equiv	15W
Incandescent Equivalent	75W

ELECTRICAL

CCT (Kelvin Temp)	5000K
Dimmable	Yes-Dimmable
Hours Rated	25000
Beam Angle (degree)	25
Color Temp	Natural Light
CRI	90+
Dimming Type	120V only, Phase cut
Operating Frequency	60Hz
Operating Temp	-20C (-4F) to +45C (+113F)
Lumens	1000L
Volts	120v
Watts	12.5W

PHYSICAL

Lamp Base	Medium
Finish	Clear
Housing Color	Silver
ANSI Base	E26
Lamp Type	PAR30LN
MOD Lamps	3.74
MOL	4.57

ADDITIONAL INFO

Warranty	5-Years
Rated For Enclosed Fixture	Yes

PACKAGING

UPC	045923294297
Case Cube	0.8425
Case Height	17.52
Case Length	6.3
Case Quantity	12
Case UPC	10045923294294
Case Weight	6.22
Case Width	13.19
EA Cube	0.0442
EA Height	4.92
EA Length	3.94
EA Quantity	1
EA Weight	0.35
EA Width	3.94
Inner Cube	0.3228
Inner Height	12.52
Inner Length	5.31
Inner Quantity	6
Inner UPC	20045923294291
Inner Weight	2.56
Inner Width	8.39
Pack Type	Box
Web Length	4.57
Web Width	3.74

COMPLIANCE

FCC Compliant	Yes
Location Rating	Wet
ROHS Compliant	Yes
Safety Listing	cULus - Listed
California Ban	Lawful for sale
DLC Approved	No
Title 20	Yes
T24 Compliant	No