



Project / Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**S29468** - 9.5 watt LED Directional Retrofit Downlight  
 - Gimbaled; 4"; 4000K; 90' Beam spread; 120 volts;  
 Dimmable



**GENERAL**

Company	SATCO
EA Height	6.69
EA Width	3.94
EA Length	6.54
Bulb Included	Integrated
Diameter	6.0
Material	Thermo Plastic (PBT)
Fixture Type	Downlight Retrofit
Status	Obsolete
Style	Contemporary
CCT Selectable	No
Wattage Selectable	No
Can Size	4 in.
Finish Family	White
Amps	0.079A
Has Camera	No
IOT Enabled	No
Power Factor	0.95
SDS Class	LED_Fixture
Indoor Outdoor	Indoor
Product Technology	LED
Incandescent Equivalent	50W

**ELECTRICAL**

CCT (Kelvin Temp)	4000K
Dimmable	Yes-Dimmable
Hours Rated	50000
Beam Angle (degree)	90
Color Temp	Cool White
CRI	90+
Dimming Type	120V only, Phase cut
Operating Temp	-4F to +113F (-20C to +45C)
Lumens	600L
Volts	120v
Watts	9.5W

**PHYSICAL**

Lamp Base	Medium Adapter
Finish	WHITE
ANSI Base	E26 Adapter
Lamp Type	Integrated LED
Fixture Shape	Round

**ADDITIONAL INFO**

Warranty	5-Years
----------	---------

**PACKAGING**

UPC	045923294686
Case Cube	1.0114
Case Height	7.68
Case Length	16.61
Case Quantity	8
Case UPC	10045923294683
Case Weight	8.51
Case Width	13.7
EA Cube	0.0998
EA Height	6.69
EA Length	6.54
EA Quantity	1
EA Weight	0.89
EA Width	3.94
Pack Type	Box
Web Height	3.47
Web Width	6.0

**COMPLIANCE**

CA Prop 65	Lead
FCC Compliant	Yes
IC Rated	Yes
Location Rating	Damp
ROHS Compliant	Yes
Safety Listing	cULus - Certified, cULus - Classified
California Ban	Non-Compliant
DLC Approved	No
Energy Star Certified	No
Title 20	No
T24 Compliant	No