



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S29599 - 12 Watt LED Downlight Retrofit; 5-6 Inch; CCT Selectable; 120 Volt; 2 Pack



GENERAL

Company	SATCO
EA Height	8.39
EA Width	5.24
EA Length	10.87
Bulb Included	Integrated
Diameter	7.48
Dimmable Text	Forward or Reverse Phase
Material	Polycarbonate (PC)
Fixture Type	Downlight Retrofit
Status	Active
Surge Protection	Built-in-surge protection - 0.5KV
Total Harmonic Distortion	<100%
CCT Selectable	Yes
Wattage Selectable	No
Can Size	5-6 in.
Finish Family	White
Amps	0.100A
Has Camera	No
IOT Enabled	No
Lens Finish	Glossy Frosted
Lens Material	Polycarbonate (PC)
Photo Cell	No Photocell
Power Factor	>0.7
SDS Class	LED_Fixture
Sloped Ceiling Compatible	No
Indoor Outdoor	Indoor
Product Technology	LED
Incandescent Equivalent	65W

ELECTRICAL

CCT (Kelvin Temp)	2700K/3000K/3500K/4000K/5000K
Dimmable	Yes-Dimmable
Hours Rated	25000
Beam Angle (degree)	110
Color Temp	Warm White to Natural Light
CRI	80+
Dimming Type	120V only, Phase cut
Operating Frequency	60Hz
Operating Temp	-4F to +104F (-20C to +40C)
Lumens	800L
Volts	120v
Watts	12W

PHYSICAL

Lamp Base	Medium
Finish	WHITE
ANSI Base	E26
Lamp Type	Integrated LED
Fixture Shape	Round

ADDITIONAL INFO

Warranty	3-Years
Installation Notes	CCT Selectable switch is on neck when fully extended out.

PACKAGING

UPC	045923295997
Case Cube	3.7456
Case Height	17.64
Case Length	22.4
Case Quantity	12
Case UPC	10045923295994
Case Weight	16.5
Case Width	16.38
EA Cube	0.2766
EA Height	8.39
EA Length	10.87
EA Quantity	1
EA Weight	1.17
EA Width	5.24
Pack Type	Box
Web Height	4.45
Web Length	7.48
Web Width	7.48

COMPLIANCE

Air Tight	No
CA Prop 65	Lead
FCC Compliant	Yes
IC Rated	Yes
IP Rating	IP20
Location Rating	Damp
NEC Compliance	Clothes Closet Certified - Reg: 410.16 (A)(3) and 410.16 (C)(5)
ROHS Compliant	Yes
Safety Listing	cETLus - Classified
California Ban	Non-Compliant
Energy Star Certified	No
Title 20	No
T24 Compliant	No
US State Ban	CA