



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S29626 - 7.5 Watt; BR30 LED; 2700K; GU24 base; 120 Volt



GENERAL

Company	SATCO
EA Height	5.51
EA Width	3.86
EA Length	3.86
Candle Power	220.0
Center Beam Candle Power	220
Lamp Filament	LED
Material	Plastic
Fixture Type	Reflector
Status	Active
Style	Contemporary
CCT Selectable	No
Wattage Selectable	No
Finish Family	White
Amps	0.063A
Has Camera	No
IOT Enabled	No
Lens Finish	Frost
Lensed	Yes
Operating Position	Universal
Power Factor	0.92
SDS Class	LED_Lamp
Indoor Outdoor	Indoor
Product Technology	LED
Incandescent Equivalent	65W

ELECTRICAL

CCT (Kelvin Temp)	2700K
Dimmable	Yes-Dimmable
Hours Rated	25000
Beam Angle (degree)	105
Color Temp	Warm White
CRI	90+
Dimming Type	120V only, Phase cut
Operating Temp	-13F to +113F (-25C to +45C)
Lumens	650L
Volts	120v
Watts	7.5W

PHYSICAL

Lamp Base	Bi Pin GU24
Finish	Frost
Housing Color	Gray
ANSI Base	GU24
Lamp Type	BR30
MOD Lamps	3.74
MOL	4.961

ADDITIONAL INFO

Warranty	5-Years
Rated For Enclosed Fixture	No

PACKAGING

UPC	045923296260
Case Cube	0.8839
Case Height	7.01
Case Length	17.13
Case Quantity	12
Case UPC	10045923296267
Case Weight	4.63
Case Width	12.72
EA Cube	0.0475
EA Height	5.51
EA Length	3.86
EA Quantity	1
EA Weight	0.29
EA Width	3.86
Inner Cube	0.3365
Inner Height	5.91
Inner Length	12.13
Inner Quantity	6
Inner UPC	20045923296264
Inner Weight	2.03
Inner Width	8.11
Pack Type	Box
Web Length	4.961
Web Width	3.74

COMPLIANCE

FCC Compliant	Yes
Location Rating	Damp
ROHS Compliant	Yes
Safety Listing	cULus - Certified, cULus - Listed
California Ban	California T24 Listed
DLC Approved	No
Title 20	Yes
T24/JA8 Compliant	Yes