



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S29717 - 25 Watt T5 LED; Miniature bi-pin base; 3500K; 50000 Average rated hours; 3200 Lumens; 120-277 Volt; Type B; Ballast Bypass; Single Ended Wiring



GENERAL

Company	SATCO
EA Height	0.8
EA Width	0.8
EA Length	45.8
Lamp Ballast Type AB	Type B
Ballasting Requirements	Ballast Bypass
Lamp Filament	LED
Fixture Type	Linear
Status	Obsolete
CCT Selectable	No
Wattage Selectable	No
Finish Family	White
Amps	0.208-0.090A
Has Camera	No
IOT Enabled	No
Lens Finish	Frost
Lensed	Yes
Nominal Length	48.0
Operating Position	Universal
Power Factor	0.95
SDS Class	LED_Lamp
Shatter Proof Type	Yes
Product Technology	LED
Fluor Equiv	54W
Incandescent Equivalent	100W

ELECTRICAL

CCT (Kelvin Temp)	3500K
Dimmable	Non-Dimmable
Hours Rated	50000
Beam Angle (degree)	240
Color Temp	Neutral White
CRI	80+
Operating Frequency	50/60Hz
Operating Temp	-20C (-4F) to +45C (+113F)
Lumens	3200L
Volts	120V-277V
Watts	25W

PHYSICAL

Lamp Base	Miniature Bi Pin
Finish	Frost
ANSI Base	G5
Lamp Type	T5
MOD Lamps	0.88
MOL	48.0

ADDITIONAL INFO

Warranty	5-Years
Installation Notes	Not for use in vapor tight fixtures.
Rated For Enclosed Fixture	Yes

PACKAGING

UPC	045923297175
Case Cube	0.7527
Case Height	5.2
Case Length	48.1
Case Quantity	25
Case UPC	10045923297172
Case Weight	12.9
Case Width	5.2
EA Cube	0.017
EA Height	0.8
EA Length	45.8
EA Quantity	1
EA Weight	0.4
EA Width	0.8
Pack Type	Sleeve
Web Length	48.0
Web Width	0.88

COMPLIANCE

FCC Compliant	Yes
Location Rating	Damp
NSF Approved	Yes
ROHS Compliant	Yes
Safety Listing	cULus - Certified, cULus - Classified, ETLus - Sanitation Recognized Component
California Ban	Lawful for sale
DLC Approved	No
Title 20	Exempt
T24 Compliant	No