



Project / Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**S29805** - 15 Watt; A19 LED; Frosted; 4000K; GU24 base; 220 deg. Beam Angle; 120 Volt



### GENERAL

Company	SATCO
EA Height	5.31
EA Width	2.44
EA Length	2.44
Dimmable Text	Forward Phase or Reverse Phase or Phase Selectable
Lamp Filament	LED
Material	Plastic
Fixture Type	Type A
Status	Active
Style	Traditional
CCT Selectable	No
Wattage Selectable	No
Finish Family	White
Amps	0.125A
Has Camera	No
IOT Enabled	No
Lens Finish	Frost
Lensed	Yes
Operating Position	Universal
Power Factor	0.94
SDS Class	LED_Lamp
Indoor Outdoor	Indoor
Product Technology	LED
Incandescent Equivalent	100W

### ELECTRICAL

CCT (Kelvin Temp)	4000K
Dimmable	Yes-Dimmable
Hours Rated	25000
Beam Angle (degree)	220
Color Temp	Cool White
CRI	80+
Dimming Type	120V only, Phase cut
Operating Frequency	60Hz
Operating Temp	-25C (-13F) to +45C (+113F)
Lumens	1600L
Volts	120v
Watts	15W

### PHYSICAL

Lamp Base	Bi Pin GU24
Finish	Frost
Housing Color	White
ANSI Base	GU24
Lamp Type	A19
MOD Lamps	2.362
MOL	4.528

### ADDITIONAL INFO

Warranty	5-Years
Rated For Enclosed Fixture	Yes

### PACKAGING

UPC	045923298059
Case Cube	0.6768
Case Height	12.32
Case Length	11.22
Case Quantity	24
Case UPC	10045923298056
Case Weight	8.97
Case Width	8.46
EA Cube	0.0183
EA Height	5.31
EA Length	2.44
EA Quantity	1
EA Weight	0.33
EA Width	2.44
Inner Cube	0.1321
Inner Height	5.63
Inner Length	7.8
Inner Quantity	6
Inner UPC	20045923298053
Inner Weight	2.12
Inner Width	5.2
Pack Type	Box
Web Length	4.528
Web Width	2.362

### COMPLIANCE

CA T20 Compliant Substitute	S28488
FCC Compliant	Yes
Location Rating	Damp
ROHS Compliant	Yes
Safety Listing	cULus - Certified, cULus - Listed
California Ban	Non-Compliant
DLC Approved	No
Title 20	No
T24 Compliant	No
US State Ban	CA