



Project / Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**S29856 - 9.5 Watt LED PL; 30K/35K/40K CCT Selectable; G24q Base; Type A**



**GENERAL**

|                           |  |
|---------------------------|--|
| Company                   | SATCO  |
| EA Height                 | 7.01   |
| EA Width                  | 1.46   |
| EA Length                 | 1.46   |
| Lamp Ballast Type AB      | Type A   |
| Ballasting Requirements   | Ballast required, check compatibility          |
| Dimmable Text             | Only Dimmable with Compatible Dimming Ballasts |
| Lamp Filament             | LED  |
| Material                  | Aluminum / Plastic                             |
| Status                    | Active   |
| Style                     | Transitional                                   |
| Total Harmonic Distortion | <20%   |
| CCT Selectable            | Yes  |
| Wattage Selectable        | No   |
| Finish Family             | White  |
| Amps                      | 0.079-0.034A                                   |
| Has Camera                | No   |
| IOT Enabled               | No   |
| Operating Position        | Universal                                      |
| Power Factor              | 0.9  |
| SDS Class                 | LED_Lamp                                       |
| Indoor Outdoor            | Indoor   |
| Product Technology        | LED  |
| Fluor Equiv               | 18W/26W/32W                                    |

**ELECTRICAL**

|                     |  |
|---------------------|--|
| CCT (Kelvin Temp)   | 3000K/3500K/4000K                              |
| Dimmable            | Yes-Dimmable                                   |
| Hours Rated         | 50000  |
| Beam Angle (degree) | 360  |
| Color Temp          | Warm to Cool White                             |
| CRI                 | 80+  |
| Dimming Type        | Only Dimmable with Compatible Dimming Ballasts |
| Operating Frequency | 50/60Hz  |
| Operating Temp      | -20C (-4F) to +45C (+113F)                     |
| Lumens              | 1100L/1150L/1200L                              |
| Volts               | Ballast Dependent                              |
| Watts               | 9.5W   |

**PHYSICAL**

|               |              |
|---------------|--------------|
| Lamp Base     | G24q (4-Pin) |
| Finish        | Frost        |
| Housing Color | White        |
| ANSI Base     | G24q         |
| Lamp Type     | PL           |
| MOD Lamps     | 1.4          |
| MOL           | 6.9          |

**ADDITIONAL INFO**

|                            |         |
|----------------------------|---------|
| Warranty                   | 5-Years |
| Rated For Enclosed Fixture | Yes     |

**PACKAGING**

|               |                |
|---------------|----------------|
| UPC           | 045923298561   |
| Case Cube     | 0.28           |
| Case Height   | 7.95           |
| Case Length   | 9.33           |
| Case Quantity | 24             |
| Case UPC      | 10045923298568 |
| Case Weight   | 6.3            |
| Case Width    | 6.42           |
| EA Cube       | 0.0086         |
| EA Height     | 7.01           |
| EA Length     | 1.46           |
| EA Quantity   | 1              |
| EA Weight     | 0.25           |
| EA Width      | 1.46           |
| Inner Cube    | 0.0            |
| Pack Type     | Box            |
| Web Length    | 6.9            |
| Web Width     | 1.4            |

**COMPLIANCE**

|                 |   |
|-----------------|---|
| FCC Compliant   | Yes   |
| Location Rating | Damp  |
| NSF Approved    | Yes   |
| ROHS Compliant  | Yes   |
| Safety Listing  | cRUus - Recognized Component, cULus - Certified, cULus - Classified |
| California Ban  | Lawful for sale   |
| Title 20        | Exempt  |
| T24 Compliant   | No  |