



S29940 - 12 Watt T8 LED; Medium bi-pin base; 4000K; 50000 Average rated hours; 1800 Lumens; Dimmable; Type A; Ballast dependent


GENERAL

Company	SATCO
EA Height	1.1
EA Width	1.1
EA Length	48.0
Lamp Ballast Type AB	Type A
Ballasting Requirements	Ballast required. Direct Replacement-for use on Instant Start, Rapid Start, Emergency, and Dimming ballasts with no rewiring required. May not be compatible with every ballast. Refer to the ballast compatability chart.
Dimmable Text	Only in Type A mode; Check Ballast MFG for Dimmer Compatibility
Lamp Filament	LED
Fixture Type	Linear
Status	Discontinued
CCT Selectable	No
Wattage Selectable	No
Has Camera	No
IOT Enabled	No
Lens Finish	Gloss
Lensed	Yes
Nominal Length	48.0
Operating Position	Universal
Power Factor	0.9
SDS Class	LED_Lamp
Product Technology	LED
Fluor Equiv	25W-32W
Incandescent Equivalent	60W

PACKAGING

UPC	045923299407
Case Cube	1.0244
Case Height	4.3
Case Length	49.6
Case Quantity	10
Case UPC	10045923299404
Case Weight	6.4
Case Width	8.3
EA Cube	0.0336
EA Height	1.1
EA Length	48.0
EA Quantity	1
EA Weight	0.6
EA Width	1.1
Pack Type	Sleeve
Web Length	48.0
Web Width	1.0

COMPLIANCE

FCC Compliant	Yes
Location Rating	Damp
ROHS Compliant	Yes
Safety Listing	cULus - Listed
California Ban	Lawful for sale
DLC Approved	No
Title 20	Exempt
T24 Compliant	No

ELECTRICAL

CCT (Kelvin Temp)	4000K
Dimmable	Yes-Dimmable
Hours Rated	50000
Beam Angle (degree)	210
Color Temp	Cool White
CRI	80+
Dimming Type	Check Ballast MFG for Dimmer Compatibility, Only in Type A mode
Operating Temp	-20C (-4F) to +45C (+113F)
Lumens	1800L
Volts	Ballast Dependent
Watts	12W

PHYSICAL

Lamp Base	Medium Bi Pin
Finish	Gloss
ANSI Base	G13
Lamp Type	T8
MOD Lamps	1.0
MOL	48.0

ADDITIONAL INFO

Warranty	5-Years
Installation Notes	Not for use in vapor tight fixtures.