



Project / Job Name:

Location:

Fixture Type:

Notes:

S30106 - LED Head Lamp with Clip; 800 Max Lumens;
USB-C Rechargeable; 3.7 Volt; 12pc Tray Pack



GENERAL

Company	SATCO
EA Height	3.0
EA Width	3.25
EA Length	2.75
Material	Aluminum
Fixture Type	Rechargeable Task
Includes	USB-A to USB-C Charging Cable
Product Notes	Replaceable Rechargeable 3.7V ion 18350 Battery; Charge Time: 2.5HRS
Status	Active
CCT Selectable	No
Wattage Selectable	No
Finish Family	Black
Additional Info	Ships in retail-ready display trays and packaging
Integrated Features	Replaceable Battery; Magnetic Base; Adjustable Head Band; Pocket Clip; Turbo
Lens Finish	Clear
Lens Material	Polycarbonate (PC)
Lensed	Yes
Portable Light Modes	High, Low, Medium, Turbo
Product Technology	LED
Serviceable Battery	Yes
Beam Distance (Ft)	292
Battery Indicator	No
Digital Display	No
Drop Impact Rating	3.28 Ft (1M)
Battery Operating Temp	+32F to +104F (0C to +40C)
Light Source Quantity	Single
Power Bank Storage	900mAh

ELECTRICAL

CCT (Kelvin Temp)	6500K
Dimmable	Yes-Dimmable
Color Temp	Daylight
CRI	50+
Dimming Type	Only dimmable via setting selection, Step Dimming
Operating Temp	+32F to +104F (0C to +40C)
Lumens	800L/300L/160L/25L
Volts	3.7V
Max Lumens	800L
Connection	USB-C Rechargeable
Charge Time	2.5hr
Battery Chemistry	Lithium-ion (Li-ion)
Replaceable Battery Type	18350
USB Type In	1 USB-C

PHYSICAL

Finish	Black / Gray / Red
Housing Color	BlackGrayRed
Mounting Procedure	Belt Clip, Magnetic Base

ADDITIONAL INFO

Warranty	1-Year
Installation Notes	Do Not Charge The Product Below 40F Or above 104F; Do Not Exceed 5V DC, 1A Charging
Portable Light Functions	White Light Function

PACKAGING

UPC	045923300073
Case Cube	1.424
Case Height	11.41
Case Length	10.24
Case Quantity	48
Case UPC	10045923300070
Case Weight	22.26
Case Width	21.06
EA Cube	0.0155
EA Height	3.0
EA Length	2.75
EA Quantity	1
EA Weight	0.3
EA Width	3.25
Inner Cube	0.224
Inner Height	3.94
Inner Length	9.53
Inner Quantity	12
Inner UPC	20045923300077
Inner Weight	9.92
Inner Width	10.31
Pack Type	Color Box
Web Height	1.29
Web Length	1.73
Web Width	2.44

COMPLIANCE

CA Prop 65	Lead
FCC Compliant	Yes
IP Rating	IPX4
ROHS Compliant	Yes
Energy Star Certified	No
T24/JA8 Compliant	No
Performance Standards	ANSI PLATO FL1