Project / Job Name:

Location:

Fixture Type:

Notes:



**S30115** - LED Heavy Duty Lantern; 1000 Max Lumens; USB-C Rechargeable; 3.7 Volt; 4pc Tray Pack

## GENERAL

| | |
|---|---|
| Company | SATCO |
| EA Height | 7.75 |
| EA Width | 4.25 |
| EA Length | 4.25 |
| Material | ABS Plastic / Polycarbonate (PC) / Thermoplastic Rubber (TPR) |
| Fixture Type | Rechargeable Lantern |
| Includes | USB-A to USB-C Charging Cable |
| Product Notes | Integrated Rechargeable 4.2V Li-ion 20650 Battery; Power Bank: 2600mAh; Charge Time: 2HRS -or- 3 C Cell Alkaline |
| Status | Active |
| CCT Selectable | No |
| Wattage Selectable | No |
| Finish Family | Black |
| Additional Info | Ships in retail-ready display trays and packaging |
| Integrated Features | Power Bank; Dual Fuel; Carry Handle; Impact Absorbing Housing; Bottom Clasp Hook; |
| Lens Finish | Clear |
| Lens Material | Polycarbonate (PC) |
| Lensed | Yes |
| Portable Light Modes | High, Low, Medium, Strobe |
| Product Technology | LED |
| Serviceable Battery | Yes |
| Beam Distance (Ft) | 72 |
| Battery Indicator | Yes |
| Digital Display | No |
| Drop Impact Rating | 3.28 Ft (1M) |
| Battery Operating Temp | +32F to +104F (0C to +40C) |
| Light Source Quantity | Single |
| Power Bank Storage | 2600mAh |

## ELECTRICAL

| | |
|---|---|
| CCT (Kelvin Temp) | 6500K |
| Dimmable | Yes-Dimmable |
| Color Temp | Daylight |
| CRI | 50+ |
| Dimming Type | Only dimmable via setting selection, Step Dimming |
| Operating Temp | +32F to +104F (0C to +40C) |
| Lumens | 1000L/650L/300L |
| Volts | 3.7V |
| Max Lumens | 1000L |
| Connection | USB-C Rechargeable |
| Charge Time | 2hr |
| Battery Chemistry | Lithium-ion (Li-ion) |
| Replaceable Battery Type | 20650 |
| USB Type In | 1 USB-C |
| USB Output Charging Power | (1) 2A 5V |
| USB Type Out | 1 USB-A 2A |
| Dual Fuel | 3 C-Cells Alkaline Batteries |

## PHYSICAL

| | |
|---|---|
| Finish | Black / Gray / Red |
| Housing Color | BlackGrayRed |
| Mounting Procedure | Hang Hook |

## ADDITIONAL INFO

| | |
|---|---|
| Warranty | 1-Year |
| Installation Notes | Do Not Charge The Product Below 40F Or above 104F; Do Not Exceed 5V DC, 1A Charging |
| Portable Light Functions | Red Light Function, White Light Function |

## PACKAGING

| | |
|---|---|
| UPC | 045923300165 |
| Case Cube | 1.2358 |
| Case Height | 10.43 |
| Case Length | 10.5 |
| Case Quantity | 8 |
| Case UPC | 10045923300162 |
| Case Weight | 13.2 |
| Case Width | 19.5 |
| EA Cube | 0.081 |
| EA Height | 7.75 |
| EA Length | 4.25 |
| EA Quantity | 1 |
| EA Weight | 1.37 |
| EA Width | 4.25 |
| Inner Cube | 0.4294 |
| Inner Height | 9.13 |
| Inner Length | 9.09 |
| Inner Quantity | 4 |
| Inner UPC | 20045923300169 |
| Inner Weight | 6.17 |
| Inner Width | 8.94 |
| Pack Type | Color Box |
| Web Height | 7.44 |
| Web Length | 4.17 |
| Web Width | 4.17 |

## COMPLIANCE

| | |
|---|---|
| CA Prop 65 | Lead |
| FCC Compliant | Yes |
| IP Rating | IPX4 |
| ROHS Compliant | Yes |
| Energy Star Certified | No |
| T24/JA8 Compliant | No |
| Performance Standards | ANSI PLATO FL1 |



© Satco Products, Inc.
All rights reserved 2026