



Project / Job Name:

Location:

Fixture Type:

Notes:

S30117 - LED Neck Light; 300 Max Lumens; USB-C Rechargeable; 3.7 Volt; 6pc Tray Pack



GENERAL

Company	SATCO
EA Height	11.5
EA Width	7.75
EA Length	3.25
Material	Aluminum / ABS Plastic
Fixture Type	Rechargeable Task
Includes	USB-A to USB-C Charging Cable
Product Notes	Integrated Rechargeable 3.7V Li-ion Battery; Charge Time: 4HRS
Status	Active
CCT Selectable	No
Wattage Selectable	No
Finish Family	Black
Additional Info	Ships in retail-ready display trays and packaging
Integrated Features	Adjustable LED Heads; Flexible Neck Support; Continuous Dimming; Magnetic Base; Tripod Mount
Lens Finish	Clear
Lens Material	Polycarbonate (PC)
Lensed	Yes
Portable Light Modes	High
Product Technology	LED
Serviceable Battery	No
Beam Distance (Ft)	98
Battery Indicator	No
Digital Display	No
Drop Impact Rating	3.28 Ft (1M)
Battery Operating Temp	+32F to +104F (0C to +40C)
Light Source Quantity	Double
Power Bank Storage	2000mAh

ELECTRICAL

CCT (Kelvin Temp)	6500K
Dimmable	Yes-Dimmable
Color Temp	Daylight
CRI	70+
Operating Temp	-4F to +104F (-20C to +40C)
Lumens	150L/300L
Volts	3.7V
Max Lumens	300L
Connection	USB-C Rechargeable
Charge Time	4hr
Battery Chemistry	LiFePO4
Replaceable Battery Type	103450
USB Type In	1 USB-C

PHYSICAL

Finish	Black / Red
Housing Color	Black/Red
Mounting Procedure	Magnetic Base, Tripod Mount

ADDITIONAL INFO

Warranty	1-Year
Installation Notes	Do Not Charge The Product Below 40F Or above 104F; Do Not Exceed 5V DC, 1A Charging
Portable Light Functions	Dimming Function, White Light Function

PACKAGING

UPC	045923300189
Case Cube	2.8923
Case Height	13.98
Case Length	17.13
Case Quantity	12
Case UPC	10045923300186
Case Weight	14.5
Case Width	20.87
EA Cube	0.1676
EA Height	11.5
EA Length	3.25
EA Quantity	1
EA Weight	0.72
EA Width	7.75
Inner Cube	1.3137
Inner Height	13.58
Inner Length	16.34
Inner Quantity	6
Inner UPC	20045923300183
Inner Weight	6.5
Inner Width	10.23
Pack Type	Color Box
Web Height	1.77
Web Length	11.02
Web Width	9.65

COMPLIANCE

CA Prop 65	Lead
FCC Compliant	Yes
IP Rating	IPX4
ROHS Compliant	Yes
Energy Star Certified	No
T24/JA8 Compliant	No
Performance Standards	ANSI PLATO FL1