



Project / Job Name:

Location:

Fixture Type:

Notes:

S39752 - 60 Watt LED HID Replacement; 5000K; Mogul extended base; Adjustable Beam Angle; Type B Ballast Bypass;100-277 Volt



GENERAL

| | |
|---------------------------|--|
| Company | SATCO |
| EA Height | 9.45 |
| EA Width | 4.96 |
| EA Length | 4.96 |
| Lamp Ballast Type AB | Type B |
| Ballasting Requirements | Ballast Bypass |
| Lamp Filament | LED |
| Material | Aluminum / Steel / Thermo Plastic (PBT) |
| Fixture Type | LED HID |
| Product Notes | Closed 260 deg; Partial 150 deg; Open 120 deg |
| Status | Active |
| Style | Utility |
| Surge Protection | Built-in surge protection - 4KV |
| Total Harmonic Distortion | <20% |
| CCT Selectable | False |
| Wattage Selectable | False |
| Finish Family | No Finish |
| Additional Info | PIR Sensor available as an accessory |
| Amps | 0.600-0.217A |
| Has Camera | False |
| IOT Enabled | False |
| Lens Finish | Clear |
| Lens Material | Thermo Plastic (PBT) |
| Lensed | True |
| Minimum Compartment Size | Width: 9.30 in. Depth: 9.30 in. Height: 9.80 in. |
| Operating Position | Base Up or Down |
| Photo Cell | Optional Add-On |
| Power Factor | >0.9 |
| SDS Class | LED_Lamp |
| Indoor Outdoor | Indoor, Outdoor |
| Product Technology | LED |
| Fluor Equiv | 85W |
| Incandescent Equivalent | 500W |

ELECTRICAL

| | |
|---------------------|----------------------------|
| CCT (Kelvin Temp) | 5000K |
| Dimmable | Non-Dimmable |
| Hours Rated | 50000 |
| Beam Angle (degree) | 120/150/260 |
| Color Temp | Natural Light |
| CRI | 80+ |
| Operating Frequency | 50/60Hz |
| Operating Temp | -20C (-4F) to +65C (+149F) |
| HID Equivalent | 250W |
| Lumens | 8400L |
| Volts | 120V-277V |
| Watts | 60W |

PHYSICAL

| | |
|---------------|----------------|
| Lamp Base | Mogul Extended |
| Finish | Clear |
| Housing Color | White |
| ANSI Base | EX39 |
| Lamp Type | Corncob |
| MOD Lamps | 4.08 |
| MOL | 7.76 |

ADDITIONAL INFO

| | |
|----------------------------|--------------------------------------|
| Warranty | 5-Years |
| Installation Notes | Not for use in vapor tight fixtures. |
| Rated For Enclosed Fixture | True |

PACKAGING

| | |
|----------------|----------------|
| UPC | 045923397523 |
| Case Cube | 2.3259 |
| Case Height | 11.02 |
| Case Length | 22.05 |
| Case Quantity | 12 |
| Case UPC | 10045923397520 |
| Case Weight | 32.8 |
| Case Width | 16.54 |
| EA Cube | 0.1345 |
| EA Height | 9.45 |
| EA Length | 4.96 |
| EA Quantity | 1 |
| EA Weight | 2.45 |
| EA Width | 4.96 |
| Inner Cube | 0.9334 |
| Inner Height | 9.92 |
| Inner Length | 15.47 |
| Inner Quantity | 6 |
| Inner UPC | 20045923397527 |
| Inner Weight | 15.8 |
| Inner Width | 10.51 |
| Pack Type | Box |
| Web Length | 7.76 |
| Web Width | 4.08 |

COMPLIANCE

| | |
|--------------------|---|
| CA Regulations | Exempt - Base Not Regulated |
| CA Status | Lawful for sale in California |
| C0 Status | Lawful for sale |
| FCC Compliant | True |
| HI Status | Lawful for sale |
| IP Rating | IP64 |
| Location Rating | Damp |
| NV Status | Lawful for sale |
| ROHS Compliant | Yes |
| Safety Listing | cULus - Certified, cULus - Classified, cULus - Listed |
| CA Compliance Text | Lawful for sale |
| VT Status | Lawful for sale |
| WA Status | Lawful for sale |
| DLC Approved | False |
| Title 20 | Exempt |
| T24 Compliant | False |