SATCO | NUVO

Project / Job Name:

Location:

Fixture Type:

Notes:

S39768 - 30 Watt LED HID Replacement; 2700K; Medium base; Adjustable Beam Angle; Type B Ballast Bypass;120-277 Volt

DAMP LOCATION · ENCLOSED FIXTURE · CLASSIFIED cULus · cULus LISTED · FC · RoHS COMPLIANT · 50,000 HOURS · TYPE B

GENERAL

Company	SATCO
EA Height	8.66
EA Width	4.65
EA Length	4.65
Lamp Ballast Type AB	Type B
Ballasting Requirements	Ballast Bypass
Lamp Filament	LED
Material	Aluminum / Steel / Thermo Plastic (PBT)
Fixture Type	LED HID
Product Notes	Closed 260 deg; Partial 150 deg; Open 120 deg
Status	Active
Style	Utility
Surge Protection	Built-in surge protection - 4KV
CCT Selectable	No
Wattage Selectable	No
Finish Family	Clear
Additional Info	PIR Sensor available as an accessory
Amps	0.300-0.108A
Has Camera	No
IOT Enabled	No
Lens Finish	Clear
Lens Material	Thermo Plastic (PBT)
Lensed	Yes
Minimum Compartment Size	Width: 8.00 in. Depth: 8.00 in. Height: 11.00 in.
Operating Position	Universal
Photo Cell	Optional Add-On
Power Factor	0.98
SDS Class	LED_Lamp
Indoor Outdoor	Indoor, Outdoor
Product Technology	LED
Fluor Equiv	55W
Incandescent Equivalent	200W

ELECTRICAL

CCT (Kelvin Temp)	2700K
Dimmable	Non-Dimmable
Hours Rated	50000
Beam Angle (degree)	120/150/260
Color Temp	Warm White
CRI	80+
Operating Frequency	50/60Hz
Operating Temp	-4F to +149F (-20C to +65C)
HID Equivalent	150W
Lumens	3840L
Volts	120V-277V
Watts	30W

PHYSICAL

Lamp Base	Medium
Finish	Clear
Housing Color	White
ANSI Base	E26
Lamp Type	Corncob
MOD Lamps	3.31
MOL	6.69

ADDITIONAL INFO

Warranty	5-Years
Installation Notes	Not for use in vapor tight fixtures.
Rated For Enclosed Fixture	Yes

PACKAGING

UPC	045923397684
Case Cube	3.8155
Case Height	19.69
Case Length	21.26
Case Quantity	24
Case UPC	10045923397681
Case Weight	44.1
Case Width	15.75
EA Cube	0.1084
EA Height	8.66
EA Length	4.65
EA Quantity	1
EA Weight	1.45
EA Width	4.65
Inner Cube	0.7585
Inner Height	9.13
Inner Length	14.53
Inner Quantity	6
Inner UPC	20045923397688
Inner Weight	10.8
Inner Width	9.88
Pack Type	Box
Web Length	6.69
Web Width	3.31

COMPLIANCE

FCC Compliant	Yes
IP Rating	IP64
Location Rating	Damp
ROHS Compliant	Yes
Safety Listing	cULus - Certified, cULus - Classified, cULus - Listed
California Ban	Lawful for sale
DLC Approved	No
Title 20	Exempt
T24/JA8 Compliant	No

© Satco Products, Inc.
All rights reserved 2026