



Project / Job Name:

Location:

Fixture Type:

Notes:

S39799 - 60 Watt LED HID Replacement; 2700K; Mogul extended base; Adjustable Beam Angle; Type B Ballast Bypass; 100-277 Volt



GENERAL

Company	SATCO
EA Height	9.45
EA Width	4.96
EA Length	4.96
Lamp Ballast Type AB	Type B
Ballasting Requirements	Ballast Bypass
Lamp Filament	LED
Material	Aluminum / Steel / Thermo Plastic (PBT)
Fixture Type	LED HID
Product Notes	Closed 260 deg; Partial 150 deg; Open 120 deg
Status	Active
Style	Utility
Surge Protection	Built-in surge protection - 4KV
Total Harmonic Distortion	<20%
CCT Selectable	False
Wattage Selectable	False
Finish Family	No Finish
Additional Info	PIR Sensor available as an accessory
Amps	0.600-0.217A
Has Camera	False
IOT Enabled	False
Lens Finish	Clear
Lens Material	Thermo Plastic (PBT)
Lensed	True
Minimum Compartment Size	Width: 9.30 in. Depth: 9.30 in. Height: 9.80 in.
Operating Position	Base Up or Down
Photo Cell	Optional Add-On
Power Factor	>0.9
SDS Class	LED_Lamp
Indoor Outdoor	Indoor, Outdoor
Product Technology	LED
Fluor Equiv	85W
Incandescent Equivalent	500W

ELECTRICAL

CCT (Kelvin Temp)	2700K
Dimmable	Non-Dimmable
Hours Rated	50000
Beam Angle (degree)	120/150/260
Color Temp	Warm White
CRI	80+
Operating Frequency	50/60Hz
Operating Temp	-20C (-4F) to +65C (+149F)
HID Equivalent	250W
Lumens	7680L
Volts	120V-277V
Watts	60W

PHYSICAL

Lamp Base	Mogul Extended
Finish	Clear
Housing Color	White
ANSI Base	EX39
Lamp Type	Corncob
MOD Lamps	4.08
MOL	7.76

ADDITIONAL INFO

Warranty	5-Years
Installation Notes	Not for use in vapor tight fixtures.
Rated For Enclosed Fixture	True