



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S39901 - 9 Watt T8 LED; 2Ft; 3500K; Medium Bi Pin base; 50000 Average rated hours; 1100 Lumens; Type B; Ballast Bypass; Single or Double Ended Wiring



GENERAL

| | |
|---------------------------|--|
| Company | SATCO |
| EA Height | 1.1 |
| EA Width | 1.1 |
| EA Length | 24.0 |
| Lamp Ballast Type AB | Type B |
| Ballasting Requirements | Ballast Bypass |
| Lamp Filament | LED |
| Material | Glass |
| Fixture Type | Linear |
| Product Notes | Built-in shock resistant circuit - (not hot until both ends are installed) |
| Status | Active |
| Style | Utility |
| Total Harmonic Distortion | 20% |
| Tube Guard Use | Yes |
| CCT Selectable | No |
| Wattage Selectable | No |
| Finish Family | White |
| Additional Info | Equivalent CCT selectable option available in S11764 |
| Amps | 0.075-0.032A |
| Has Camera | No |
| IOT Enabled | No |
| Lens Finish | Gloss White |
| Lens Material | Glass |
| Nominal Length | 24.0 |
| Operating Position | Universal |
| Power Factor | 0.9 |
| SDS Class | LED_Lamp |
| Indoor Outdoor | Indoor, Outdoor |
| Product Technology | LED |
| Fluor Equiv | 17W |
| Incandescent Equivalent | 40W |

ELECTRICAL

| | |
|---------------------|----------------------------|
| CCT (Kelvin Temp) | 3500K |
| Hours Rated | 50000 |
| Beam Angle (degree) | 210 |
| Color Temp | Neutral White |
| CRI | 80+ |
| Operating Frequency | 50/60Hz |
| Operating Temp | -20C (-4F) to +45C (+113F) |
| Lumens | 1100L |
| Volts | 120V-277V |
| Watts | 9W |

PHYSICAL

| | |
|---------------|---------------|
| Lamp Base | Medium Bi Pin |
| Finish | Gloss White |
| Housing Color | White |
| ANSI Base | G13 |
| Lamp Type | T8 |
| MOD Lamps | 1.1 |
| MOL | 23.78 |

ADDITIONAL INFO

| | |
|----------------------------|--------------------------------------|
| Warranty | 5-Years |
| Installation Notes | Not for use in vapor tight fixtures. |
| Rated For Enclosed Fixture | Yes |

PACKAGING

| | |
|---------------|----------------|
| UPC | 045923399015 |
| Case Cube | 0.5208 |
| Case Height | 6.0 |
| Case Length | 25.0 |
| Case Quantity | 25 |
| Case UPC | 10045923399012 |
| Case Weight | 6.88 |
| Case Width | 6.0 |
| EA Cube | 0.0168 |
| EA Height | 1.1 |
| EA Length | 24.0 |
| EA Quantity | 1 |
| EA Weight | 0.28 |
| EA Width | 1.1 |
| Pack Type | Sleeve |
| Web Length | 23.78 |
| Web Width | 1.1 |

COMPLIANCE

| | |
|-----------------|---|
| DLC ID | PLSLJY8NLUXI |
| FCC Compliant | Yes |
| Location Rating | Damp |
| NSF Approved | Yes |
| ROHS Compliant | Yes |
| Safety Listing | cRUus - Recognized Component, cULus - Certified, cULus - Classified |
| California Ban | Lawful for sale |
| DLC Approved | Yes |
| Title 20 | Exempt |
| T24 Compliant | No |