



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S39906-TF - 17 Watt T8 LED; 4Ft; 4000K; Medium Bi Pin base; 50000 Average rated hours; 2200 Lumens; Type B; Ballast Bypass; Single or Double Ended Wiring; Shatterproof coated



GENERAL

| | |
|---------------------------|---------------------|
| Company | SATCO |
| EA Height | 1.1 |
| EA Width | 1.1 |
| EA Length | 48.0 |
| Lamp Ballast Type AB | Type B |
| Ballasting Requirements | Ballast Bypass |
| Lamp Filament | LED |
| Material | Glass |
| Fixture Type | Linear |
| Status | Active |
| Style | Utility |
| Total Harmonic Distortion | 20% |
| CCT Selectable | No |
| Wattage Selectable | No |
| Finish Family | White |
| Amps | 0.142-0.061A |
| Has Camera | No |
| IOT Enabled | No |
| Lens Finish | Gloss White |
| Lens Material | Glass |
| Nominal Length | 48.0 |
| Operating Position | Universal |
| Power Factor | 0.9 |
| SDS Class | LED_Lamp |
| Shatter Proof Type | Shatterproof coated |
| Indoor Outdoor | Indoor, Outdoor |
| Product Technology | LED |
| Fluor Equiv | 45W |
| Incandescent Equivalent | 90W |

PACKAGING

| | |
|---------------|--------|
| Case Cube | 1.0208 |
| Case Height | 6.0 |
| Case Length | 49.0 |
| Case Quantity | 25 |
| Case Weight | 14.4 |
| Case Width | 6.0 |
| EA Cube | 0.0336 |
| EA Height | 1.1 |
| EA Length | 48.0 |
| EA Quantity | 1 |
| EA Weight | 0.58 |
| EA Width | 1.1 |
| Pack Type | Sleeve |
| Web Length | 47.78 |
| Web Width | 1.1 |

COMPLIANCE

| | |
|-------------------|--------------------|
| FCC Compliant | Yes |
| Location Rating | Damp |
| NSF Approved | Yes |
| ROHS Compliant | Yes |
| Safety Listing | cULus - Classified |
| California Ban | Lawful for sale |
| DLC Approved | No |
| Title 20 | Exempt |
| T24/JA8 Compliant | No |

ELECTRICAL

| | |
|---------------------|-----------------------------|
| CCT (Kelvin Temp) | 4000K |
| Dimmable | Non-Dimmable |
| Hours Rated | 50000 |
| Beam Angle (degree) | 210 |
| Color Temp | Cool White |
| CRI | 80+ |
| Operating Frequency | 50/60Hz |
| Operating Temp | -4F to +113F (-20C to +45C) |
| Lumens | 2200L |
| Volts | 120V-277V |
| Watts | 17W |

PHYSICAL

| | |
|---------------|---------------|
| Lamp Base | Medium Bi Pin |
| Finish | Gloss White |
| Housing Color | White |
| ANSI Base | G13 |
| Lamp Type | T8 |
| MOD Lamps | 1.1 |
| MOL | 47.78 |

ADDITIONAL INFO

| | |
|----------------------------|--------------------------------------|
| Warranty | 5-Years |
| Installation Notes | Not for use in vapor tight fixtures. |
| Rated For Enclosed Fixture | Yes |