



Project / Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**S39916** - 14 Watt T8 LED; 4Ft; 5000K; Medium Bi Pin base; 50000 Average rated hours; 1800 Lumens; Type B; Ballast Bypass; Single or Double Ended Wiring



**GENERAL**

Company	SATCO
EA Height	48.0
EA Width	1.1
EA Length	1.1
Lamp Ballast Type AB	Type B
Ballasting Requirements	Ballast Bypass
Lamp Filament	LED
Material	Glass
Fixture Type	Linear
Product Notes	Built-in shock resistant circuit - (not hot until both ends are installed)
Status	Active
Style	Utility
Total Harmonic Distortion	20%
Tube Guard Use	Yes
CCT Selectable	No
Wattage Selectable	No
Finish Family	White
Additional Info	Equivalent CCT selectable option available in S11766
Amps	0.117-0.051A
Has Camera	No
IOT Enabled	No
Lens Finish	Gloss White
Lens Material	Glass
Nominal Length	48.0
Operating Position	Universal
Power Factor	0.9
SDS Class	LED_Lamp
Indoor Outdoor	Indoor, Outdoor
Product Technology	LED
Fluor Equiv	25W/28W/30W/32W
Incandescent Equivalent	75W

**ELECTRICAL**

CCT (Kelvin Temp)	5000K
Hours Rated	50000
Beam Angle (degree)	210
Color Temp	Natural Light
CRI	80+
Operating Frequency	50/60Hz
Operating Temp	-4F to +113F (-20C to +45C)
Lumens	1800L
Volts	120V-277V
Watts	14W

**PHYSICAL**

Lamp Base	Medium Bi Pin
Finish	Gloss White
Housing Color	White
ANSI Base	G13
Lamp Type	T8
MOD Lamps	1.1
MOL	47.78

**ADDITIONAL INFO**

Warranty	5-Years
Installation Notes	Not for use in vapor tight fixtures.
Rated For Enclosed Fixture	Yes

**PACKAGING**

UPC	045923399169
Case Cube	1.0208
Case Height	6.0
Case Length	49.0
Case Quantity	25
Case UPC	10045923399166
Case Weight	14.4
Case Width	6.0
EA Cube	0.0336
EA Height	48.0
EA Length	1.1
EA Quantity	1
EA Weight	0.58
EA Width	1.1
Pack Type	Sleeve
Web Length	47.78
Web Width	1.1

**COMPLIANCE**

DLC ID	PL5U5EECCTSI
FCC Compliant	Yes
Location Rating	Damp
NSF Approved	Yes
ROHS Compliant	Yes
Safety Listing	cRUus - Recognized Component, cULus - Certified, cULus - Classified
California Ban	Lawful for sale
DLC Approved	Yes
Title 20	Exempt
T24/JA8 Compliant	No