



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S39920 - 15 Watt 4 Foot T8 LED; 5000K CCT; Medium Bi Pin Base; Ballast Bypass; Single or Double Ended Wiring; 120-277 Volt



GENERAL

Company	SATCO
EA Height	1.0
EA Width	1.0
EA Length	47.78
Lamp Ballast Type AB	Type B
Ballasting Requirements	Ballast Bypass
Center Beam Candle Power	210
Lamp Filament	LED
Material	Glass
Fixture Type	Linear
Status	Active
Style	Utility
Surge Protection	Built-in surge protection - 1KV
Total Harmonic Distortion	<20%
CCT Selectable	No
Wattage Selectable	No
Finish Family	White
Amps	0.125-0.054A
Has Camera	No
IOT Enabled	No
Nominal Length	48.0
Operating Position	Universal
Power Factor	>0.9
SDS Class	LED_Lamp
Indoor Outdoor	Indoor and Outdoor
Product Technology	LED
Fluor Equiv	25W/28W/30W/32W
Incandescent Equivalent	75W

ELECTRICAL

CCT (Kelvin Temp)	5000K
Dimmable	Non-Dimmable
Hours Rated	50000
Beam Angle (degree)	210
Color Temp	Natural Light
CRI	80+
Operating Frequency	50/60Hz
Operating Temp	-4F to +113F (-20C to +45C)
Lumens	2200L
Volts	120V-277V
Watts	15W

PHYSICAL

Lamp Base	Medium Bi Pin
Finish	Gloss White
Housing Color	White
ANSI Base	G13
Lamp Type	T8
MOD Lamps	1.0
MOL	47.78

ADDITIONAL INFO

Warranty	5-Years
Installation Notes	Not for use in vapor tight fixtures.
Rated For Enclosed Fixture	Yes

PACKAGING

UPC	045923399206
Case Cube	0.9505
Case Height	5.75
Case Length	48.66
Case Quantity	25
Case UPC	10045923399203
Case Weight	13.59
Case Width	5.87
EA Cube	0.0277
EA Height	1.0
EA Length	47.78
EA Quantity	1
EA Weight	0.5
EA Width	1.0
Pack Type	Sleeve
Web Length	47.78
Web Width	1.0

COMPLIANCE

DLC ID	S-1MX4D8
FCC Compliant	Yes
Location Rating	Damp
NSF Approved	Yes
ROHS Compliant	Yes
Safety Listing	cRUus - Recognized Component, cULus - Classified
California Ban	Lawful for sale
DLC Approved	Yes
Title 20	Exempt
T24/JA8 Compliant	No