



Project / Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**S39926** - 12 Watt T8 LED; 3Ft; 3000K; Medium Bi Pin base; 50000 Average rated hours; 1400 Lumens; Type B; Ballast Bypass; Single or Double Ended Wiring



### GENERAL

Company	SATCO
EA Height	1.1
EA Width	1.1
EA Length	36.0
Lamp Ballast Type AB	Type B
Ballasting Requirements	Ballast Bypass
Lamp Filament	LED
Material	Glass
Fixture Type	Linear
Product Notes	Built-in shock resistant circuit - (not hot until both ends are installed)
Status	Active
Style	Utility
Total Harmonic Distortion	20%
Tube Guard Use	Yes
CCT Selectable	No
Wattage Selectable	No
Finish Family	White
Additional Info	Equivalent CCT selectable option available in S11765
Amps	0.100-0.0433A
Has Camera	No
IOT Enabled	No
Lens Finish	Gloss White
Lens Material	Glass
Nominal Length	36.0
Operating Position	Universal
Power Factor	0.9
SDS Class	LED_Lamp
Indoor Outdoor	Indoor, Outdoor
Product Technology	LED
Fluor Equiv	25W
Incandescent Equivalent	50W

### ELECTRICAL

CCT (Kelvin Temp)	3000K
Hours Rated	50000
Beam Angle (degree)	210
Color Temp	Warm White
CRI	80+
Operating Frequency	50/60Hz
Operating Temp	-4F to +113F (-20C to +45C)
Lumens	1400L
Volts	120V-277V
Watts	12W

### PHYSICAL

Lamp Base	Medium Bi Pin
Finish	Gloss White
Housing Color	White
ANSI Base	G13
Lamp Type	T8
MOD Lamps	1.1
MOL	35.78

### ADDITIONAL INFO

Warranty	5-Years
Installation Notes	Not for use in vapor tight fixtures.
Rated For Enclosed Fixture	Yes

### PACKAGING

UPC	045923399268
Case Cube	0.7708
Case Height	6.0
Case Length	37.0
Case Quantity	25
Case UPC	10045923399265
Case Weight	11.33
Case Width	6.0
EA Cube	0.0252
EA Height	1.1
EA Length	36.0
EA Quantity	1
EA Weight	0.45
EA Width	1.1
Pack Type	Sleeve
Web Length	35.78
Web Width	1.1

### COMPLIANCE

DLC ID	PLU0IB3BFNJ0
FCC Compliant	Yes
Location Rating	Damp
NSF Approved	Yes
ROHS Compliant	Yes
Safety Listing	cRUus - Recognized Component, cULus - Certified, cULus - Classified
California Ban	Lawful for sale
DLC Approved	Yes
Title 20	Exempt
T24/JA8 Compliant	No