



Project / Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**S39934** - 12 Watt T8 LED; Medium bi-pin base; 3000K; 50000 Average rated hours; 1700 Lumens; Type A; Ballast dependent



**GENERAL**

Company	SATCO
EA Height	1.0
EA Width	1.0
EA Length	48.0
Lamp Ballast Type AB	Type A
Ballasting Requirements	Ballast required. Direct Replacement- for use on Instant Start and Rapid Start ballasts with no rewiring required. May not be compatible with every ballast. Refer to the ballast compatibility chart
Lamp Filament	LED
Fixture Type	Linear
Status	Obsolete
CCT Selectable	No
Wattage Selectable	No
Finish Family	White
Has Camera	No
IOT Enabled	No
Lens Finish	Gloss White
Lensed	Yes
Nominal Length	48.0
Operating Position	Universal
Power Factor	0.9
SDS Class	LED_Lamp
Product Technology	LED
Fluor Equiv	25W-32W
Incandescent Equivalent	60W

**PACKAGING**

UPC	045923399343
Case Cube	0.9871
Case Height	5.9
Case Length	49.0
Case Quantity	25
Case UPC	10045923399340
Case Weight	14.4
Case Width	5.9
EA Cube	0.0278
EA Height	1.0
EA Length	48.0
EA Quantity	1
EA Weight	0.5
EA Width	1.0
Pack Type	Sleeve
Web Length	48.0
Web Width	1.0

**COMPLIANCE**

FCC Compliant	Yes
Location Rating	Damp
NSF Approved	Yes
ROHS Compliant	Yes
Safety Listing	cULus
California Ban	Lawful for sale
DLC Approved	No
Title 20	Exempt
T24/JA8 Compliant	No

**ELECTRICAL**

CCT (Kelvin Temp)	3000K
Dimmable	Yes-Dimmable
Hours Rated	50000
Beam Angle (degree)	210
Color Temp	Warm White
CRI	80+
Dimming Type	Check Ballast MFG for Dimmer Compatibility, Only in Type A mode
Operating Temp	-4F to +113F (-20C to +45C)
Lumens	1700L
Volts	Ballast Dependent
Watts	12W

**PHYSICAL**

Lamp Base	Medium Bi Pin
Finish	Gloss White
ANSI Base	G13
Lamp Type	T8
MOD Lamps	1.0
MOL	48.0

**ADDITIONAL INFO**

Warranty	5-Years
Installation Notes	Not for use in vapor tight fixtures.
Rated For Enclosed Fixture	Yes