



Project / Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**S39934** - 12 Watt T8 LED; Medium bi-pin base; 3000K; 50000 Average rated hours; 1700 Lumens; Type A; Ballast dependent



**GENERAL**

|                         |   |
|-------------------------|---|
| Company                 | SATCO   |
| EA Height               | 1.0   |
| EA Width                | 1.0   |
| EA Length               | 48.0  |
| Lamp Ballast Type AB    | Type A  |
| Ballasting Requirements | Ballast required. Direct Replacement- for use on Instant Start and Rapid Start ballasts with no rewiring required. May not be compatible with every ballast. Refer to the ballast compatibility chart |
| Dimmable Text           | Only in Type A mode; Check Ballast MFG for Dimmer Compatibility   |
| Lamp Filament           | LED   |
| Fixture Type            | Linear  |
| Status                  | Obsolete  |
| CCT Selectable          | No  |
| Wattage Selectable      | No  |
| Finish Family           | White   |
| Has Camera              | No  |
| IOT Enabled             | No  |
| Lens Finish             | Gloss White   |
| Lensed                  | Yes   |
| Nominal Length          | 48.0  |
| Operating Position      | Universal   |
| Power Factor            | 0.9   |
| SDS Class               | LED_Lamp  |
| Product Technology      | LED   |
| Fluor Equiv             | 25W-32W   |
| Incandescent Equivalent | 60W   |

**ELECTRICAL**

|                     |                            |
|---------------------|----------------------------|
| CCT (Kelvin Temp)   | 3000K                      |
| Dimmable            | Yes-Dimmable               |
| Hours Rated         | 50000                      |
| Beam Angle (degree) | 210                        |
| Color Temp          | Warm White                 |
| CRI                 | 80+                        |
| Operating Temp      | -20C (-4F) to +45C (+113F) |
| Lumens              | 1700L                      |
| Volts               | Ballast Dependent          |
| Watts               | 12W                        |

**PHYSICAL**

|           |               |
|-----------|---------------|
| Lamp Base | Medium Bi Pin |
| Finish    | Gloss White   |
| ANSI Base | G13           |
| Lamp Type | T8            |
| MOD Lamps | 1.0           |
| MOL       | 48.0          |

**ADDITIONAL INFO**

|                            |                                      |
|----------------------------|--------------------------------------|
| Warranty                   | 5-Years                              |
| Installation Notes         | Not for use in vapor tight fixtures. |
| Rated For Enclosed Fixture | Yes                                  |

**PACKAGING**

|                |                |
|----------------|----------------|
| UPC            | 045923399343   |
| Case Cube      | 0.9871         |
| Case Height    | 5.9            |
| Case Length    | 49.0           |
| Case Quantity  | 25             |
| Case UPC       | 10045923399340 |
| Case Weight    | 14.4           |
| Case Width     | 5.9            |
| EA Cube        | 0.0278         |
| EA Height      | 1.0            |
| EA Length      | 48.0           |
| EA Quantity    | 1              |
| EA Weight      | 0.5            |
| EA Width       | 1.0            |
| Inner Cube     | 0.0            |
| Inner Height   | 0.0            |
| Inner Length   | 0.0            |
| Inner Quantity | 0              |
| Inner Weight   | 0.0            |
| Inner Width    | 0.0            |
| Pack Type      | Sleeve         |
| Web Length     | 48.0           |
| Web Width      | 1.0            |

**COMPLIANCE**

|                 |                 |
|-----------------|-----------------|
| FCC Compliant   | Yes             |
| Location Rating | Damp            |
| NSF Approved    | Yes             |
| ROHS Compliant  | Yes             |
| Safety Listing  | cULus           |
| California Ban  | Lawful for sale |
| DLC Approved    | No              |
| Title 20        | Exempt          |
| T24 Compliant   | No              |