



Project / Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**S4535** - 60 Watt C15 Incandescent; Clear; 1500 Average rated hours; Medium base; 120 Volt; Shatter Proof



**GENERAL**

Company	SATCO
EA Height	4.13
EA Width	1.88
EA Length	1.88
Fixture Type	Candle
Status	Discontinued
CCT Selectable	No
Wattage Selectable	No
Finish Family	Clear
Amps	0.500A
IOT Enabled	No
Lens Finish	Clear
Lensed	Yes
Operating Position	Universal
SDS Class	Incandescent_Lamp
Shatter Proof Type	PFA Coating
Product Technology	Incandescent

**ELECTRICAL**

CCT (Kelvin Temp)	2700K
Dimmable	Yes-Dimmable
Hours Rated	1500
Beam Angle (degree)	360
Color Temp	Warm White
CRI	100
Lumens	800L
Volts	120v
Watts	60W

**PHYSICAL**

Lamp Base	Medium
Finish	Clear
ANSI Base	E26
Lamp Type	C15
MOD Lamps	1.88
MOL	4.5

**ADDITIONAL INFO**

Installation Notes	Shatterproof coated incandescent lamps should not be used in close proximity to live poultry or birds
--------------------	---

**PACKAGING**

UPC	045923045356
Case Cube	0.2547
Case Height	4.63
Case Length	9.75
Case Quantity	25
Case UPC	10045923045353
Case Weight	1.75
Case Width	9.75
EA Cube	0.0084
EA Height	4.13
EA Length	1.88
EA Quantity	1
EA Weight	0.07
EA Width	1.88
Pack Type	Box
Web Length	4.5
Web Width	1.88

**COMPLIANCE**

CA T20 Compliant Substitute	S2840
CA Prop 65	PFAS
NSF Approved	Yes
ROHS Compliant	Yes
Safety Listing	Not Applicable
California Ban	Non-Compliant
DLC Approved	No
Title 20	No
T24/JA8 Compliant	No
US State Ban	CA, MA, NV